

TP-Link INSIGHT S345 Bullet IP security camera Outdoor 2688 x 1520 pixels Wall



Brand : TP-Link

Product code: INSIGHT S345(6MM)

Product name : INSIGHT S345

- 4MP Super-High Definition and 24h Full-Color
- People & Vehicle Analytics§
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Active Defense and Two-Way Audio
- IP67 Waterproof
- H.265+ Compression Technology


VIGI 4MP Outdoor Full-Color Bullet Network Camera, 1/2.7", 1/3 to 1/10000 s, F1.6, 2688 x 1520, CBR, VBR, BLC/3D DNR/HLC/SmartIR, 120 dB, 12V DC ± 5%, Max. 9.7 W, 5.5 mm Coaxial Power Plug, PoE: 802.3af/at, class 0, Max. 10.7 W, IP67, 184 x 74 x 74 mm, 0.525 kg, White

TP-Link INSIGHT S345. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Wall, Product colour: White, Form factor: Bullet. Lens viewing angle, horizontal: 52,7°, Lens viewing angle, vertical: 29°, Lens viewing angle, diagonal: 60,8°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Detect distance: 120 m, Observe distance: 50 m, Recognize distance: 24 m




Performance		Audio	
Type *	IP security camera	Audio output channels	1.0 channels
Placement supported *	Outdoor	Audio formats supported	G.711 A-law
Connectivity technology *	Wired	Sample rate	8 kHz
Maximum operating distance	120 m	Built-in microphone	✓
Wide Dynamic Range (WDR)	✓	Number of microphones	1
Day/night mode	✓	Audio detection	✓
Infrared (IR) cut-off filter	✓	Bit rate range	0 - 64 Kbit/s
Remote viewing	✓	Network	
Dynamic range	120 dB	Ethernet LAN *	✓
Design		Networking standards	IEEE 802.3af, IEEE 802.3at
Form factor *	Bullet	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
Mounting type *	Wall	Wi-Fi *	✗
Product colour *	White	Bluetooth *	✗
Housing material	Metal	Live view	✓
Protection features	Waterproof	Storage	
International Protection (IP) code	IP67	Compatible memory cards	MicroSD (TransFlash)
Weatherproof	✓	Maximum memory card size	512 GB
Camera		Ports & interfaces	
Minimum illumination	0 lx	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, horizontal	52,7°	Security	
Lens viewing angle, vertical	29°	Built-in siren	✓
Lens viewing angle, diagonal	60,8°	Password protection	✓
Tilt angle range	0 - 90°	Video motion detection	✓
Camera shutter speed	1/3 to 1/10000	IP address filtering	✓
Image sensor		HTTPS encryption	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Alert notification type	Push notification
Progressive scan	✓	Motion sensor	✓
Sensor type *	CMOS	Mirror	✓
Lens system			
Detect distance	120 m		
Observe distance	50 m		
Recognize distance	24 m		

Lens system		Security	
Maximum aperture number	1.6	Human and vehicle targets classification	✓
Night vision		Management features	
Night vision *	✓	Web-based management	✓
LED type	IR/White	Web browser	✓
Video		Cloud-managed *	✓
Maximum resolution *	2688 x 1520 pixels	Reset button	✓
Total megapixels *	4 MP	Power	
Video compression formats	H.264, H.264+, H.265, H.265+	Power source type *	DC, PoE
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440, 2688 x 1520	Power consumption (Power over Ethernet (PoE))	10.7 W
Video recording	✓	DC output voltage	12
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Operational conditions	
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Operating temperature (T-T)	-30 - 60 °C
Bit rate	Main Stream: 256 Kbps to 6 Mbps, Sub-Stream: 64 Kbps to 512 Kbps	Storage temperature (T-T)	-40 - 60 °C
Back Light Compensation (BLC)	✓	Operating relative humidity (H-H)	0 - 95%
Highlight Compensation (HLC)	✓	Storage relative humidity (H-H)	0 - 95%
Digital Wide Dynamic Range (DWDR)	✓	Weight & dimensions	
Audio		Width	74 mm
Built-in speaker(s)	✓	Height	74 mm
Audio system	2-way	Length	184 mm
Audio input channels	1.0 channels	Weight	525 g
Packaging data		Packaging content	
Package type		Number of cameras *	1
Box		Mounting kit	✓
		Screws included	✓
		Drilling template included	✓
		Manual	✓



8885020628081

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.