

## CyberPower PDU15MV20F power distribution unit (PDU) 20 AC outlet(s) 0U Black

**Brand :** CyberPower

**Product code:** PDU15MV20F

**Product name :** PDU15MV20F

20 NEMA 5-15R, 0U, 120V AC, 50/60Hz



[CyberPower PDU15MV20F power distribution unit \(PDU\) 20 AC outlet\(s\) 0U Black:](#)

The CyberPower 20-outlet (20 Front) 0U vertical rack mount metered power distribution unit (PDU15MV20F) provides 120V 15A output. It distributes power to 20 NEMA 5-15R receptacles from a single NEMA 5-15P plug, with unfiltered electrical pass-through. The current draw for connected equipment is displayed in amps on the front LCD for real-time load monitoring. Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 10-foot AC power cord. It supports vertical, horizontal and wall mount installation, includes a cord retention tray and is ETL/RoHS certified. A lifetime warranty ensures that this PDU is free of defects in design, assembly, material or workmanship.



- 20 NEMA 5-15R (20 Front) output receptacles
- 15-amp electrical capacity with circuit breaker
- 120V AC - 50/60Hz
- 48" 0U vertical rack mount
- Front LCD for real-time load monitoring
- 10-ft. power cord

<b>Design</b>		<b>Power</b>	
PDU types *	Metered	Maximum current *	15 A
Rack capacity *	0U	Nominal output voltage	120 V
Mounting	Horizontal/Vertical	Power protection features	Overload
Product colour	Black		
Display	LCD		
<b>Ports &amp; interfaces</b>		<b>Certificates</b>	
AC outlets quantity *	20 AC outlet(s)	Compliance certificates	RoHS
Power plug	NEMA 5-15P	Certification	UL1363 ETL, CSA C22.2
AC outlet types *	NEMA 5-15R		
<b>Features</b>		<b>Operational conditions</b>	
Cable length	3.05 m	Operating temperature (T-T)	0 - 35 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
<b>Management features</b>		<b>Weight &amp; dimensions</b>	
Monitoring	Current	Weight (imperial)	0.0567 kg (0.125 lbs)
<b>Power</b>		Dimensions (W x D x H) (imperial)	
Nominal input voltage *	120 V		44.5 x 57.1 x 1219.2 mm (1.75 x
AC input frequency	50 - 60 Hz		2.25 x 48")



649532901081

0649532901081

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.