

Tripp Lite AVR750U uninterruptible power supply (UPS) Line-Interactive 0.75 kVA 450 W 12 AC outlet(s)

Brand : Tripp Lite

Product code: AVR750U

Product name : AVR750U

Tripp Lite AVR750U. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 450 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 12 AC outlet(s). Battery voltage: 12 V, Typical backup time at full load: 3 min, Typical backup time at half load: 11 min. Form factor: Tower, Product colour: Black, Housing material: Acrylonitrile butadiene styrene (ABS). Width: 190 mm, Depth: 304.8 mm, Height: 105.2 mm



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Tower
Output power capacity *	0.75 kVA	Housing material	Acrylonitrile butadiene styrene (ABS)
Output power *	450 W	Cable length	1.5 m
Input operation voltage (min) *	89 V	Product colour *	Black
Input operation voltage (max) *	145 V	LED indicators	✓
Output operation voltage (min)	110 V	Certification	UL1778, CSA, NOM, FCC
Output operation voltage (max)	120 V	Operational conditions	
Automatic Voltage Regulation (AVR)	✓	Operating temperature (T-T)	0 - 40 °C
Maximum current	15 A	Storage temperature (T-T)	-15 - 50 °C
Surge energy rating	316 J	Operating relative humidity (H-H)	0 - 90%
EMI/RFI noise filtering	✓	Operating altitude	0 - 3048 m
Surge protection	✓	Technical details	
Audible alarm(s)	✓	Sustainability certificates	RoHS, ENERGY STAR
Country of origin	China	Weight & dimensions	
Ports & interfaces		Width	190 mm
AC outlet types	NEMA 5-15R	Depth	304.8 mm
Power plug	NEMA 5-15P	Height	105.2 mm
AC outlets quantity	12 AC outlet(s)	Weight	7.18 kg
USB port	✓	Package width	160 mm
USB 2.0 ports quantity	1	Package depth	381 mm
Battery		Package height	272 mm
Battery voltage	12 V	Package weight	8.13 kg
Typical backup time at full load	3 min	Logistics data	
Typical backup time at half load	11 min	Master (outer) case width	398 mm
Cold start	✓	Master (outer) case length	499.9 mm
		Master (outer) case height	300 mm
		Master (outer) case gross weight	23.6 kg
		Products per master (outer) case	3 pc(s)
		Master (outer) case GTIN (EAN/UPC)	10037332211481



0037332211484



037332211484

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.