

## NETGEAR 26-Port PoE Gigabit Ethernet Smart Switch (GS324TP)

**Brand :** NETGEAR

**Product code:** GS324TP-100NAS



**Product name :** 26-Port PoE Gigabit Ethernet Smart Switch (GS324TP)

24x RJ-45, 2x SFP, 16K MAC, 512 KB, VLAN, QoS, LACP, IGMP, PoE+  
NETGEAR 26-Port PoE Gigabit Ethernet Smart Switch (GS324TP). Switch type: Managed. Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 16000 entries, Switching capacity: 52 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Power connector: AC-in jack. Power over Ethernet (PoE)

| Management features                             |   | Security                                       |             |
|---|---|--|-------------|
| Switch type *                                   | Managed   | IGMP snooping                                  | ✓           |
| Quality of Service (QoS) support                | ✓   | Loop protection                                | ✓           |
| ARP inspection                                  | ✓   | <b>Design</b>                                  |             |
| Ports & interfaces                              |   | Rack mounting *                                | ✗           |
| Basic switching RJ-45 Ethernet ports quantity * | 24  | Product colour                                 | Black       |
| SFP module slots quantity                       | 2   | LED indicators                                 | ✓           |
| Power connector                                 | AC-in jack  | Number of fans                                 | 2 fan(s)    |
| Network   |   | Performance                                    |             |
| Networking standards *                          | IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3at, IEEE 802.3az, IEEE 802.3x | Noise level                                    | 32.8 dB     |
| Port mirroring                                  | ✓   | Firmware upgradeable                           | ✓           |
| Full duplex                                     | ✓   | Power  |             |
| Flow control support                            | ✓   | AC input voltage                               | 100 - 240 V |
| Link aggregation                                | ✓   | AC input frequency                             | 50 - 60 Hz  |
| Broadcast storm control                         | ✓   | Input current                                  | 5 A         |
| Rate limiting                                   | ✓   | Power consumption (max)                        | 229.9 W     |
| Spanning tree protocol                          | ✓   | Power over Ethernet (PoE)                      |             |
| Auto-negotiation                                | ✓   | Power over Ethernet (PoE) *                    | ✓           |
| VLAN support                                    | ✓   | Power over Ethernet plus (PoE+) ports quantity | 24          |
| Virtual LAN features                            | Port-based VLAN, Private VLAN, Voice VLAN   | Total Power over Ethernet (PoE) budget         | 190 W       |
| Number of VLANs                                 | 256   | Operational conditions                         |             |
| Data transmission                               |   | Operating temperature (T-T)                    | 0 - 45 °C   |
| Switching capacity *                            | 52 Gbit/s   | Weight & dimensions                            |             |
| MAC address table *                             | 16000 entries   | Width  | 330 mm      |
| Store-and-forward                               | ✓   | Depth  | 206 mm      |
| Jumbo frames support                            | ✓   | Height   | 43 mm       |
| Security  |   | Weight   | 2.69 kg     |
| DHCP features                                   | DHCP client   | Packaging content                              |             |
| Access Control List (ACL)                       | ✓   | Cables included                                | AC          |



0606449135602



606449135602

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.