

CyberPower PDU33105 power distribution unit (PDU) 44 AC outlet(s) 0U Black

Brand : CyberPower
Product code: PDU33105
Product name : PDU33105

- Phase: 3-Phase
 - Notifications: Email, SMS Text, and SNMP Trap
 - Amps: 30A (Derated to 24A)
 - Volts: 208V
 - Frequency: 50/60Hz
 - Input plug type: NEMA L21-30P
 - Outlets: (2) NEMA 5-20R + (36) IEC-320 C13 + (6) IEC-320 C19
 - Size: 0U Rackmount
 - Cord Length (ft): 10
- NEMA 5-20R, IEC-320 C13, IEC-320 C19, RJ45, LCD, LED, 50/60Hz, IPv4, TCP/IP, UDP, SNMPv1, HTTP, NTP, DNS, Telnet, DHCP, SMTP, FTP, IPv6, SNMPv3, HTTPs, SSH, SSL, TLS, LDAP(S), RADIUS, Syslog, CLI, Windows AD, 7.12 kg, 56 x 1791 x 56 mm
- CyberPower PDU33105. PDU types: Monitored, Rack capacity: 0U, Type: Three-phase. AC outlets quantity: 44 AC outlet(s), AC outlet types: NEMA 5-20R, Power plug: IEC 320. LED indicators: Link, Status, Cable length: 3 m. Supported network protocols: IPv4, IPv6, HTTP, TLS, DNS, TCP/IP, DHCP, FTP, SNMPv1, NTP, Telnet, SMTP, SNMPv3, HTTPs, SSH, SSL,..., Management protocols: UDP, Syslog, CLI, Windows AD, Firmware upgradeable via: USB. Nominal input voltage: 120 - 208 V, Maximum current: 30 A, AC input frequency: 50 - 60 Hz



Design		Power	
PDU types *	Monitored	Nominal input voltage *	120 - 208 V
Type	Three-phase	AC input frequency	50 - 60 Hz
Rack capacity *	0U	Maximum current *	30 A
Housing material	Metal	Power protection features	Overload
Product colour	Black	Certificates	
Display	LCD	Compliance certificates	RoHS
On/off switch	✔	Operational conditions	
Ports & interfaces		Operating temperature (T-T)	-5 - 60 °C
AC outlets quantity *	44 AC outlet(s)	Operating relative humidity (H-H)	0 - 95%
Power plug	IEC 320	Operating altitude	0 - 3499 m
AC outlet types *	NEMA 5-20R	Operating temperature (T-T)	23 - 140 °F
Ethernet LAN (RJ-45) ports	2	Weight & dimensions	
USB ports quantity	1	Width	56 mm
Features		Depth	56 mm
LED indicators	Link, Status	Height	1791 mm
Cable length	3 m	Weight	7.12 kg
Management features		Packaging data	
Supported network protocols	IPv4, IPv6, HTTP, TLS, DNS, TCP/IP, DHCP, FTP, SNMPv1, NTP, Telnet, SMTP, SNMPv3, HTTPs, SSH, SSL, LDAP(S), RADIUS	Package weight	10.5 kg
Management protocols	UDP, Syslog, CLI, Windows AD	Package width	175.3 mm
Firmware upgradeable	✔	Package depth	160 mm
Firmware upgradeable via	USB	Package height	2034.5 mm



0649532932832



649532932832

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.