ENHANCED FOR EFFICIENCY



FEATURES

3rd Generation Dual Chamber Pump – Newly designed dual chamber pump for improved overall cooling efficiency and performance.

Enlarged Cooling Surface Area – Increased surface area on the radiator for better heat dissipation and enhanced cooling performance

New SickleFlow 120 RGB Fan – Improved lighting and performance using Air Balance fan blades, with new refreshed exterior design.

Reinforced Sealing – Using unique formula from high Industrial Grade EPDM material to increase the lifespan and reinforce the sealing to prevent leakage

RGB Lighting Solution – Fully customizable RGB lighting that is certified compatible with all major motherboard manufacturers (Wired Controller also included).

PACKING INFORMATION

EAN code	4719512095584
UPC code	884102067884
Net weight	0.649 kg
Gross weight	1.41 kg
Package dimension (L x W X H)	239 x 207 x 137 mm
Carton dimension (L x W x H)	635 x 495 x 310 mm
Units/CTN	12

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20′	2880	24	N/A
40′	5760	24	N/A
40 HQ	6720	28	N/A

The Perfect Start

CoolerMaster MasterLiquid ML120L RGB V2 is a refreshed design from the popular MasterLiquid Lite Series that elevates the exterior design elements. The Pump of the ML120L RGB V2 has been enhanced with the newly designed 3rd Gen. Dual Chamber Pump that improves the overall cooling efficiency of the AIO water cooler. The radiator surface area has been enlarged to increase the surface area for heat dissipation for optimized cooling performance. The ML120L RGB V2 will included the latest SickleFlow 120 RGB fan with a brand new design and Air Balance fan blades that is quieter than before without compromising on air flow and pressure.


SPECIFICATIONS

Product Nam	е	MasterLiquid ML120L V2 RGB	
Product Num	ber	MLW-D12M-A18PC-R2	
Exterior Color		Black	
CPU Socket	Intel	LGA 2066/ 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156	
CI O SOCKET	AMD	AM4 / AM3+ / AM3 / AM2+/ AM2 / FM2+ / FM2 / FM1	
Dadiata:	Material	Aluminum	
Radiator	Dimensions (L x W x H)	157 x 119.6 x 27.2mm (6.2 x 4.7 x 1.1 inch)	
	Dimensions (L x W x H)	79.9 x 76 x 47.1mm(3.1 x 3 x 1.9 inch)	
	MTTF (Hours)	70,000 hours	
Pump	Noise Level (dBA)	<15dBA	
Pullip	Connector	3-Pin	
	Rated Voltage (VDC)	12	
	Power Consumption (W)	2.36 W (LED 2.21W)	
	Dimensions (L x W x H)	120 x 120 x 25mm (4.7 x 4.7 x 1 inch)	
	Quantity (pcs)	1	
	LED Type	RGB	
	Speed (RPM)	650~1800RPM±10%	
Fan	Airflow (CFM)	62 CFM (Max)	
	Noise Level (dBA)	8~27 dBA	
	Pressure (mmH2O)	2.5 mmH ₂ O (Max)	
	Life Expectancy (Hours)	160,000 hours	
	Power Connector	4-Pin	
	Rated Voltage (VDC)	12	
	Rated Current (A)	0.15A (LED 0.2A)	
TDP (W)		180 W	
RAM Clearance Warranty		N/A	
		2 years	



FEATURES







New Dual Chamber Pump

3rd Generation dual chamber pump designed for better performance and overall efficiency.

Larger Surface Area

Increased surface area of the fins on the radiator for better heat dissipation.

RGB Ready

Refresh of the Masterliquid Lite comes in RGB allowing you to control the color mood of you build. Certified compatible with all major motherboard manufacturers'.



Wired Controller Included

Perfect starter kit for those whom do not have RGB ports



Reinforced Sealing

Improved manufacturing process which will increase the lifespan of your cooler and also prevent leaking.



SickleFlow 120 RGB

New SickleFlow 120 RGB with improved performance and new exterior outlook