StarTech.com Gigabit Ethernet Single Mode Fiber Media Converter SC 40 km - 1000 Mbps






Brand: StarTech.com Product code: ET91000SM402

Product name: Gigabit Ethernet Single Mode Fiber Media

Converter SC 40 km - 1000 Mbps

Gigabit Ethernet Single Mode Fiber Media Converter SC 40 km - 1000 Mbps StarTech.com Gigabit Ethernet Single Mode Fiber Media Converter SC 40 km - 1000 Mbps. Maximum data transfer rate: 2000 Mbit/s, Converter input interface: 1000Base-T, Converter output interface: 1000Base-LX, 1000Base-SX. Maximum transfer distance: 40000 m, Wavelength: 1310 nm, Fiber mode structure: Single-mode. Product colour: Black. Fiber optic connector: SC, Connectivity technology: Wired. Output voltage: 12 V, Output current: 1 A, Power consumption (typical): 4 W

| Network | | Power | |
|---|---|---|-------------------------|
| Maximum data transfer rate * Converter input interface Converter output interface Ethernet interface type | 2000 Mbit/s 1000Base-T 1000Base-LX, 1000Base-SX Gigabit Ethernet | Output current Power consumption (typical) External power adapter | 1 A 4 W ✓ |
| | | Weight & dimensions | |
| Ethernet LAN data rates Auto MDI/MDI-X | 1000 Mbit/s | Weight | 600 g |
| Duplex system | Full, Half | Operational conditions | |
| Performance | | Operating temperature (T-T) | 0 - 60 °C |
| Maximum transfer distance * Wavelength * | 40000 m 1310 nm | Storage temperature (T-T) Operating relative humidity (H-H) | -10 - 70 °C 10 - 90% |
| Fiber mode structure | Single-mode | Packaging content | |
| Mean time between failures (MTBF) | 65000 h | Manual | ✓ |
| Features | | Packaging data | |
| Internal * | × | Package width | 140 mm |
| Plug and Play | ✓ | Package depth | 205 mm |
| Product colour | Black | Package height | 91 mm |
| Ports & interfaces | | Package weight | 700 g |
| Connectivity technology | Wired | Certificates | |
| Ethernet LAN (RJ-45) ports | 1 | Compliance certificates | RoHS |
| Fiber ports quantity | 1 | Certification | CE, FCC |
| Fiber optic connector * | SC | Logistics data | |
| DC-in jack | ✓ | Harmonized System (HS) code | 85176990 |
| Power | | Other features | |
| Output voltage | 12 V | Dimensions (WxDxH) Full duplex | 95 x 160 x 20 mm ✓ |





065030846219

0065030846219



5054533430716

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.