

NETGEAR GSM4212P Managed L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

Brand : NETGEAR

Product code: GSM4212P-100NAS

Product name : GSM4212P



AV Line M4250-10G2F-PoE+ (GSM4212P) 8x1G PoE+ 125W 2x1G and 2xSFP Managed Switch
 NETGEAR GSM4212P. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 10. Full duplex. MAC address table: 16000 entries, Switching capacity: 24 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ad, IEEE... Power over Ethernet (PoE). Rack mounting, Form factor: 1U



Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L2/L3	Design	
Quality of Service (QoS) support	✓	Rack mounting *	✓
Ports & interfaces		Form factor	1U
Basic switching RJ-45 Ethernet ports quantity *	10	Product colour	Black
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	LED indicators	PoE, Power, Status
SFP module slots quantity	2	Performance	
Network		Built-in processor	✓
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3x	Processor model	ARM Cortex-A9
	10G support *	Processor frequency	1250 MHz
Full duplex	✓	Internal memory	2048 MB
Link aggregation	✓	Noise level	30.06 dB
Broadcast storm control	✓	Mean time between failures (MTBF)	778769 h
Rate limiting	✓	Power	
Spanning tree protocol	✓	Power source *	PoE
VLAN support	✓	Power consumption (typical)	163.9 W
Virtual LAN features	MAC address-based VLAN, Private VLAN	Power over Ethernet (PoE)	
Number of VLANs	4096	Power over Ethernet (PoE) *	✓
Data transmission		Power over Ethernet plus (PoE+) ports quantity	8
Switching capacity *	24 Gbit/s	Power over Ethernet (PoE) power per port	30 W
Throughput	17.86 Mpps	Total Power over Ethernet (PoE) budget	150 W
MAC address table *	16000 entries	Operational conditions	
Store-and-forward	✓	Operating temperature (T-T)	0 - 50 °C
Latency (1 Gbps)	2.27 µs	Storage temperature (T-T)	-20 - 70 °C
Number of queues	8	Operating relative humidity (H-H)	0 - 90%
Jumbo frames support	✓	Storage relative humidity (H-H)	0 - 95%
Jumbo frames	12000	Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 3000 m
		Heat dissipation	559.555 BTU/h

Data transmission		Weight & dimensions	
Packet buffer memory	16 MB	Width	440 mm
Security		Depth	200 mm
DHCP features	DHCP Option 82, DHCP relay, DHCP server, DHCP snooping, DHCPv6 client, DHCPv6 relay, DHCPv6 server, DHCPv6 snooping	Height	43.2 mm
Access Control List (ACL)	✓	Weight	2.85 kg
IGMP snooping	✓		
SSH/SSL support	✓		
Loop protection	✓		
BPDU filtering/protection	✓		
Authentication	MAC-based authentication		
Authentication type	RADIUS		



0606449149531



606449149531

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.