




Kingston Technology FURY 128GB 6400MT/s DDR5 ECC Reg CL32 DIMM (Kit of 8) Renegade Pro EXPO

Brand : Kingston Technology

Product family: FURY

Product code:
KF564R32RBEK8-128

Product name : 128GB
6400MT/s DDR5 ECC Reg CL32
DIMM (Kit of 8) FURY Renegade
Pro EXPO



- Overclocking with ECC
- Increased efficiency
- Intel® XMP 3.0 certified
- AMD EXPO™ certified
- Plug N Play*

128GB 6400MT/s DDR5 ECC Reg CL32 DIMM (Kit of 8) FURY Renegade Pro EXPO

Kingston Technology FURY 128GB 6400MT/s DDR5 ECC Reg CL32 DIMM (Kit of 8) Renegade Pro EXPO.


Component for: PC/Server, Internal memory: 128 GB, Memory layout (modules x size): 8 x 16 GB,

Internal memory type: DDR5, Memory form factor: 288-pin DIMM, CAS latency: 32, ECC, Product colour: Black

| Features | | Operational conditions | |
|---|-----------------------|----------------------------------|--------------|
| Buffered memory type | Registered (buffered) | Storage temperature (T-T) | -55 - 100 °C |
| On-Die ECC | ✓ | Technical details | |
| CAS latency | 32 | Compliance certificates | RoHS |
| Internal memory * | 128 GB | Sustainability | |
| Memory layout (modules x size) * | 8 x 16 GB | Sustainability compliance | ✓ |
| Internal memory type * | DDR5 | Doesn't contain | Halogen |
| Memory data transfer rate * | 6400 MT/s | Weight & dimensions | |
| Component for * | PC/Server | Width | 3.8 mm |
| Memory form factor * | 288-pin DIMM | Depth | 133.3 mm |
| ECC * | ✓ | Height | 31.2 mm |
| Memory voltage | 1.4 V | Weight | 145.6 g |
| AMD Extended Profiles for Overclocking (EXPO) | ✓ | Packaging data | |
| AMD Extended Profiles for Overclocking (EXPO) version | 1.1 | Package width | 104.1 mm |
| SPD profile | ✓ | Package depth | 167.6 mm |
| Country of origin | China, Taiwan | Package height | 35.6 mm |
| Product colour | Black | Package weight | 190.51 g |
| Cooling type | Heatsink | Logistics data | |
| Lead plating | Gold | Master (outer) case width | 207 mm |
| JEDEC standard | ✓ | Master (outer) case length | 469.9 mm |
| | | Master (outer) case height | 105.4 mm |
| | | Master (outer) case gross weight | 2.21 kg |
| | | Products per master (outer) case | 10 pc(s) |
| Operational conditions | | | |
| Operating temperature (T-T) | 0 - 95 °C | | |



0740617340341



740617340341

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.