## GIGABYTE R283 AMD SoC LGA 6096 Rack (2U)

**Brand : GIGABYTE Product code:** R283-Z90-AAD2

**Product name:** R283

DDR5, 24x DIMM, 3.5", 2.5", SoC

GIGABYTE R283. Motherboard chipset: AMD SoC, Processor socket: LGA 6096, Processor manufacturer: AMD. Supported memory types: DDR4-SDRAM, Supported DIMM module capacities: 256GB, Maximum RDIMM memory: 256 GB. Storage drive sizes supported: 2.5,3.5", Supported storage drive types: HDD & SSD, Supported storage drive interfaces: Serial ATA, Serial Attached SCSI (SAS). On-board graphics card model: Aspeed AST2500. Ethernet LAN data rates: 10,100,1000 Mbit/s, LAN controller: Intel® 1350-AM2



| Processor   |   | Expansion slots   |   |
|---|---|---|---|
| Built-in processor *  Motherboard chipset *  Processor socket *  Processor manufacturer  Processor family  Processor generation | AMD SoC<br>LGA 6096<br>AMD<br>AMD EPYC<br>AMD EPYC 9004 | PCI Express slots version PCI slots PCI Express x24 Riser Super slots | 4.0<br>7<br>1   |
|   |   | Features  |   |
|   |   | Trusted Platform Module (TPM) Trusted Platform Module (TPM)           | 1   |
| Number of processors supported *  | 2   | version   | 2.0   |
| Memory  |   | Backplanes support  | ✓   |
| Number of DIMM slots * Supported memory types * Supported DIMM godyla consisting  | 32<br>DDR4-SDRAM  | Logistics data  |   |
|   |   | Harmonized System (HS) code   | 84714100  |
| Supported DIMM module capacities  Maximum RDIMM memory  | 256 GB  | Design  |   |
| Supported RDIMM clock speeds  | 4800 MHz  | Chassis type *  | Rack (2U)   |
| Memory channels   | Octa-channel  | LED indicators  | HDD, LAN, Status                                      |
| Storage   |   | Power   |   |
| Number of storage drives supported  | 12  | Power supply *  | 2000 W  |
| *   |   | Number of main power supplies   | 2   |
| Hot-swap HDD bays *   | <b>/</b>  | Redundant power supply (RPS) support                                  | ✓   |
| Number of 2.5" bays   | 12  | AC input voltage  | 110 - 240 V   |
| Number of 3.5" bays   | 12  | DC output current (+5 V)  | 81 A  |
| Storage drive sizes supported   | 2.5,3.5"  | DC output current (+12 V)   | 163 A   |
| Supported storage drive types   | HDD & SSD<br>Serial ATA, Serial Attached SCSI           | •   | 103 //  |
| Supported storage drive interfaces  | (SAS)   | Operational conditions Operating temperature (T-T)                    | 10 - 35 °C  |
| RAID levels   | 0, 1, 5, 10   | Storage temperature (T-T)   | -40 - 60 °C   |
| Graphics  |   | Operating relative humidity (H-H)                                     | 8 - 80%   |
| On-board graphics card model  | Aspeed AST2500  | Storage relative humidity (H-H)                                       | 20 - 95%  |
| Network   |   | Weight & dimensions   |   |
| Ethernet LAN  | ✓   | Width   | 438 mm  |
| Ethernet LAN data rates   | 10,100,1000 Mbit/s                                      | Depth   | 87 mm   |
| LAN controller  | Intel® I350-AM2   | Height  | 730 mm  |
| Ports & interfaces  |   | Packaging data  |   |
| Ethernet LAN (RJ-45) ports * VGA (D-Sub) ports quantity   | 2   | Packaging content   | 1 x R282-Z96 system 2 x CPU<br>heatsinks 1 x Rail kit |
| COM ports quantity  | 1   | Package width   | 982 mm  |
| posto quantity  | -   | Package depth   | 588 mm  |
|   |   | Package height  | 268 mm  |

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.