

## TP-Link Omada PoE++ Injector

**Brand :** TP-Link

**Product family:** Omada

**Product code:** POE380S

**Product name :** Omada PoE++  
Injector



- 2x 10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps/10 Mbps RJ45 ports ensure faster transmission
- Complies with IEEE802.3af/at/bt standards, supplies up to 90 W
- Reduces infrastructure costs by transmitting data and power simultaneously via an Ethernet cable
- Automatically determines and supplies the exact power to meet the device's need
- Wall-mounting and desktop design accommodates most installation scenarios
- Plug & Play installation, no configuration required
- Integrated power supply
- Durable metal casing

1 x 10 Gbps RJ45 In, 1 x 10 Gbps RJ45 Out, 90 W max out, 155x70x42 mm

[TP-Link Omada PoE++ Injector:](#)



### 90W 10G PoE++ Injector

Unlocks peak performance for your 10G/Multi-Gig bandwidth and devices


### 10G Ports Ensure Faster Connection

Auto-negotiation for 6-speed (10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps /10 Mbps)


### Auto Detect the Required Power, Up to 90 W

Standard 802.3af/at/bt for Various Powered Devices

Network		Certificates	
Ethernet interface type	10 Gigabit Ethernet	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Ethernet LAN data rates	10,100,2500,10000 Mbit/s	<b>Sustainability</b>	
Cabling technology	1000/10000	Sustainability compliance	✓
Power over Ethernet (PoE)	✓	<b>Operational conditions</b>	
Networking standards	IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u	Operating temperature (T-T)	0 - 45 °C
<b>Features</b>		Operating relative humidity (H-H)	10 - 90%
Product colour	Black	Storage temperature (T-T)	-40 - 70 °C
LED indicators	PoE, Power	Storage relative humidity (H-H)	5 - 90%
<b>Ports &amp; interfaces</b>		<b>Weight &amp; dimensions</b>	
RJ-45 input ports	1	Width	155 mm
RJ-45 output ports	1	Depth	70 mm
		Height	42 mm
<b>Power</b>		<b>Packaging content</b>	
AC adapter input voltage	100 - 240 V	Number of products included	1 pc(s)
AC adapter frequency	50 - 60 Hz	Quick installation guide	✓
Input current	1.6 A		




4895252506341



4895252506358



0840030711848



840030711848

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.