



DELL Pro Plus P1425 computer monitor 35.6 cm (14") 1920 x 1200 pixels WUXGA LCD Silver



Brand : DELL

Product family: Pro Plus

Product code: DELL-P1425

Product name : P1425

- 35.6cm (14") WUXGA 1920 x 1200 Edge LED IPS

- 7ms, 16:10, 400cd/m², 1500:1

- USB

35.6cm (14") WUXGA 1920 x 1200 Edge LED IPS, 16:10, 400cd/m², 16.7M, 7ms, 178°/178°, 1500:1

[DELL Pro Plus P1425 computer monitor 35.6 cm \(14"\) 1920 x 1200 pixels WUXGA LCD Silver:](#)

Expand your productivity while on-the-go with this versatile 14-inch portable monitor.

DELL Pro Plus P1425. Display diagonal: 35.6 cm (14"), Display resolution: 1920 x 1200 pixels, HD type: WUXGA, Display technology: LCD, Response time: 7 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub. VESA mounting. Product colour: Silver

Display		Ergonomics	
Display diagonal *	35.6 cm (14")	Height adjustment *	✗
Display resolution *	1920 x 1200 pixels	Tilt adjustment	✓
HD type *	WUXGA	Tilt angle range	10 - 90°
Native aspect ratio *	16:10	On Screen Display (OSD)	✓
Display technology *	LCD	Plug and Play	✓
Panel type *	IPS		
LED backlight	✓	Power	
Backlight type	Edge LED	Energy efficiency class (SDR) *	B
Touchscreen *	✗	Energy efficiency class (HDR) *	Not available
Display brightness (typical)	400 cd/m ²	Energy consumption (SDR) per 1000 hours *	5 kWh
Response time *	7 ms	Power consumption (typical) *	5.4 W
Response time measurement type	GTG (Gray to Gray)	Power consumption (standby) *	0.3 W
Anti-glare screen	✓	Power consumption (max)	7 W
Screen shape *	Flat	Power consumption (off)	0.3 W
	640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 768, 1280 x 800, 1366 x 768, 1440 x 900, 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+)	Power supply type	External
Supported graphics resolutions		Energy efficiency scale	A to G
Supported video modes	480p, 576p, 720p, 1080p	Operational conditions	
Contrast ratio (typical) *	1500:1	Operating temperature (T-T)	0 - 40 °C
Maximum refresh rate *	60 Hz	Storage temperature (T-T)	-20 - 60 °C
Viewing angle, horizontal	178°	Operating relative humidity (H-H)	10 - 90%
Viewing angle, vertical	178°	Storage relative humidity (H-H)	5 - 90%
Display number of colours *	16.7 million colours	Operating altitude	0 - 5000 m
Pixel pitch	0.15708 x 0.15708 mm	Non-operating altitude	0 - 12192 m
Pixel density	162 ppi	Weight & dimensions	
Horizontal scan range	30 - 118 kHz	Width (with stand)	315.1 mm
Vertical scan range	56 - 60 Hz	Depth (with stand)	14.7 mm
Viewable size, horizontal	30.2 cm	Height (with stand)	223.5 mm
Viewable size, vertical	18.9 cm	Width (without stand)	315.1 mm
Display diagonal (metric)	35.57 cm	Depth (without stand)	4.6 mm
		Height (without stand)	223.5 mm

Display		Weight & dimensions	
Surface hardness	3H	Weight (without stand)	570 g
Colour gamut standard	sRGB	Bezel width (side)	5.95 mm
sRGB coverage (typical)	100%	Bezel width (top)	1.36 cm
Performance		Bezel width (bottom)	2.14 cm
NVIDIA G-SYNC *	✗	Packaging data	
AMD FreeSync *	✗	Package weight	1.24 kg
Windows operating systems supported	Windows 10, Windows 11	Packaging content	
Mac operating systems supported	✓	Stand included	✓
Multimedia		Sustainability	
Built-in speaker(s) *	✗	Sustainability certificates	ENERGY STAR
Built-in camera *	✗	Doesn't contain	Arsenic, Mercury, PVC/BFR
Design		Carbon footprint	
Product colour *	Silver	Total carbon footprint (kg of CO2e)	71.5
Ports & interfaces		Carbon emissions, manufacturing (kg of CO2e)	40.54
Built-in USB hub *	✓	Carbon emissions, logistics (kg of CO2e)	2.36
USB upstream port type	USB Type-C	Carbon emissions, energy usage (kg of CO2e)	27.46
Number of upstream ports	2	Carbon emissions, end-of-life (kg of CO2e)	1.14
Number of USB Type-C upstream ports quantity	2	PAIA version	GaBi version 1, 2024
USB Type-C DisplayPort Alternate Mode	✓	Other features	
HDMI *	✗	USB ports quantity	2
Headphone out *	✗	Compliance certificates	RoHS
HDCP	✓	Supplied AC adapter type	AC
HDCP version	1.4		
Ergonomics			
VESA mounting *	✓		
Cable lock slot *	✗		



5397184962565



0884116492665



884116492665

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.