

## Tripp Lite ECO850LCD uninterruptible power supply (UPS) Standby (Offline) 0.85 kVA 425 W 12 AC outlet(s)

**Brand :** Tripp Lite

**Product code:** ECO850LCD

**Product name :** ECO850LCD

Tripp Lite ECO850LCD. UPS topology: Standby (Offline), Output power capacity: 0.85 kVA, Output power: 425 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 12 AC outlet(s). Typical backup time at full load: 2.3 min, Typical backup time at half load: 9 min. Form factor: Compact, Product colour: Black, Cable length: 1.8 m. Width: 130 mm, Depth: 309.9 mm, Height: 85.1 mm



Features		Design	
UPS topology *	Standby (Offline)	Form factor *	Compact
Output power capacity *	0.85 kVA	Cable length	1.8 m
Output power *	425 W	Product colour *	Black
Waveform *	Pure sine	Display type	LCD
Input operation voltage (min) *	110 V	LED indicators	✓
Input operation voltage (max) *	120 V	<b>Operational conditions</b>	
Input frequency *	60 Hz	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (min)	120 V	Storage temperature (T-T)	-15 - 45 °C
Output operation voltage (max)	120 V	Operating relative humidity (H-H)	0 - 90%
Output frequency	50/60 Hz	Operating altitude	0 - 3048 m
Maximum current	15 A	<b>Technical details</b>	
Surge energy rating	316 J	Sustainability certificates	RoHS, ENERGY STAR
ECO mode	✓	<b>Weight &amp; dimensions</b>	
EMI/RFI noise filtering	✓	Width	130 mm
Surge protection	✓	Depth	309.9 mm
Surge protection features	Digital Subscriber Line (DSL), Network, Telephone	Height	85.1 mm
Country of origin	Vietnam	Weight	3.09 kg
Ports & interfaces		Package width	151.9 mm
AC outlet types	NEMA 5-15R	Package depth	379 mm
Power plug	NEMA 5-15P	Package height	198.9 mm
AC outlets quantity	12 AC outlet(s)	Package weight	3.39 kg
USB port	✓	<b>Packaging data</b>	
USB 2.0 ports quantity	1	Cables included	USB cable
Modem (RJ-11) ports	1	Manual	✓
Ethernet LAN (RJ-45) ports	2	<b>Logistics data</b>	
Battery		Master (outer) case width	395 mm
Typical backup time at full load	2.3 min	Master (outer) case length	475 mm
Typical backup time at half load	9 min	Master (outer) case height	428 mm
Cold start	✓	Master (outer) case gross weight	21.4 kg
		Products per master (outer) case	6 pc(s)

**Logistics data**

Master (outer) case GTIN (EAN/UPC) 10037332211139



0037332211132



037332211132

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-APR-2024. Prints or copies of Information are only valid on the printed Publication date