



Thunderbolt 3 Passive Cable (M/M) - 20 Gbps, 5A 100W Power Delivery, 4K/60 Hz, 1.5 m (5 ft.), Black

MODEL NUMBER: MTB3-01M5-5A-B











Connects 2 Thunderbolt 3 devices, including MacBooks and Chromebooks, for charging them or transmitting 4K video at 20 Gbps speeds.

Features

Passive Cable Connects Thunderbolt 3 Devices, Including MacBooks and ChromebooksThis Thunderbolt 3 cable allows you to connect one Thunderbolt 3-enabled device to another, including MacBooks, Ultrabooks, Chromebooks, external hard drives and docking stations. It transmits full 4K x 2K (3840 x 2160 at 60 Hz) DisplayPort video and works with existing DisplayPort monitors. The cable's 1.5-meter length makes it easy to carry in your briefcase or laptop bag for quick video connections and file transfers on the go.

Charges Devices and Transfers Data 2 Times Faster Than USB 3.1 Gen 2The MTB3-01M5-5A-B supports bidirectional Thunderbolt 3 data transfer speeds up to a whopping 20 Gbps, which is twice as fast as USB 3.1 Gen 2. The PD Charging cable also provides power output up to 5 amps (100 watts), which is sufficient for fast-charging, syncing and powering most large-capacity devices.

Reversible Thunderbolt 3 Connectors Attach in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible Thunderbolt 3 male connectors plug into a Thunderbolt 3 or USB-C port in either direction for a fumble-free connection every time. Note: both ends must be connected to a Thunderbolt 3 port to achieve 20 Gbps transfer speeds.

Highlights

- Thunderbolt 3 cable is compatible with all USB-C and Thunderbolt 3 devices
- Supports Thunderbolt 3 speeds up to 20 Gbps—2x faster than USB 3.1 Gen 2
- Provides 5A (100W) power output for charging and powering large-capacity mobile devices
- Reversible Thunderbolt 3 plugs connect in either direction for immediate no-fuss use
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Connect your laptop to a docking station or hub with a USB-C or Thunderbolt 3 port
- Bridge two Thunderbolt 3enabled notebooks for migrating data or setting up a peer-to-peer network
- Stream 4K video from your MacBook or Chromebook to a monitor or television with a DisplayPort input
- Connect a DisplayPort monitor or laptop to an external GPU box for playing graphicsintensive 4K video games

System Requirements

 Devices with Thunderbolt 3 or USB-C ports (20 Gbps speeds possible only through Thunderbolt 3)

Package Includes

 MTB3-01M5-5A-B Thunderbolt 3 Cable, M/M, 1.5 m, Black

Specifications

OVERVIEW		
UPC Code	037332242020	
Technology	DisplayPort; Thunderbolt	
VIDEO		





Power Consumption (Watts) 0.02	Max Supported Video Resolution	3840 x 2160 (4K x 2K) @ 60 Hz	
Power Consumption (Watts) 0.02			
USB Power Delivery (PD) Charging Support 2.0 LUSB Power Delivery (PD) Charging Specification 2.0 Power Consumption Detail Under 20mW PHYSICAL Color Black Cable Jacket Color Black Cable Jacket Color 5 (apple 1) Cable Length (ft.) 5 Cable Length (ft.) 5 Cable Length (m) 1.52 Cable Length (mn) 150 Unit Dimensions (ftwd / in.) 0.000 x 0.000 x 0.000 ENVIRONMENTAL Operating Temperature Range 32° to 122°F (0° to 50°C) Storage Temperature Range 32° to 185°F (-20° to 85°C) Relative Humidity 25% – 85% RH Power Provided to Connected Device(s) 5A (100W) Power Delivery CONNECTIONS Side 8 - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side 9 - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Yorksper Conflication 1.2 <td>POWER</td> <td></td>	POWER		
Vas Power Delivery (PD) Charging 2.0	Power Consumption (Watts)	0.02	
Power Consumption Detail	USB Power Delivery (PD) Charging Support	Yes	
Physical Black Color Black Cable Jacket Color Black Cable Jacket Color Black Cable Outer Diameter (OD) 4/- 4.8 mm Cable Chapth (fit.) 5 Cable Length (m) 1.52 Cable Length (m) 150 Cable Length (cm) 150 Cable Length	USB Power Delivery (PD) Charging Specification	2.0	
Color Black Cable Jacket Color Black Cable Outer Diameter (OD) 4/- 4.8 mm Cable Length (ft.) 5 Cable Length (m) 1.52 Cable Length (cm) 150 Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000 EEVIRONMENTAL Operating Temperature Range 32° to 122°F (0° to 50°C) Storage Temperature Range -4° to 185°F (-20° to 85°C) Relative Humidity 25% - 85% RH Power Provided to Connected Device(s) 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1,2	Power Consumption Detail	Under 20mW	
Cable Jacket Color Black Cable Outer Diameter (OD) +/- 4.8 mm Cable Length (ft.) 5 Cable Length (m) 1.52 Cable Length (cm) 150 Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000 ENVIRONMENTAL Operating Temperature Range 32° to 122°F (°° to 50°C) Storage Temperature Range 32° to 122°F (°° to 50°C) Storage Temperature Range 4° to 185°F (*20° to 85°C) Relative Humidity 25% ~ 85% RH Power Provided to Connected Device(s) 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Displayport Specification 1.2	PHYSICAL		
Cable Outer Diameter (OD) +/- 4.8 mm Cable Length (ft.) 5 Cable Length (m) 1.52 Cable Length (cm) 150 Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000 ENVIRONMENTAL Operating Temperature Range 32" to 122"F (0" to 50"C) Storage Temperature Range -4" to 185"F (-20" to 85"C) Relative Humidity 25% ~ 85% RH Power Provided to Connected byorice(s) 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Color	Black	
Cable Length (ft.) 5 Cable Length (m) 1.52 Cable Length (m) 59.1 Cable Length (m) 150 Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000 ENVIRONMENTAL Operating Temperature Range 32° to 122°F (0° to 50°C) Storage Temperature Range 4° to 185°F (-20° to 85°C) Relative Humidity 25% - 85% RH Power Provided to Connected 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Cable Jacket Color	Black	
Cable Length (m) 1.52 Cable Length (in.) 59.1 Cable Length (cm) 150 Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000 ENVIRONMENTAL Operating Temperature Range 32° to 122°F (0° to 50°C) Storage Temperature Range 4º to 185°F (-20° to 85°C) Relative Humidity 25% ~ 85% RH Power Provided to Connected Device(s) 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Cable Outer Diameter (OD)	+/- 4.8 mm	
Cable Length (in.) 59.1 Cable Length (cm) 150 Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000 ENVIRONMENTAL Operating Temperature Range 32° to 122°F (0° to 50°C) Storage Temperature Range -4° to 185°F (-20° to 85°C) Relative Humidity 25% ~ 85% RH Power Provided to Connected Device(s) 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Cable Length (ft.)	5	
Cable Length (cm) 150 Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000 ENVIRONMENTAL Operating Temperature Range 32° to 122°F (0° to 50°C) Storage Temperature Range -4° to 185°F (-20° to 85°C) Relative Humidity 25% ~ 85% RH Power Provided to Connected 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Cable Length (m)	1.52	
Unit Dimensions (hwd / in.) ENVIRONMENTAL Operating Temperature Range 32° to 122°F (0° to 50°C) Storage Temperature Range -4° to 185°F (-20° to 85°C) Relative Humidity 25% - 85% RH Power Provided to Connected Device(s) 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Cable Length (in.)	59.1	
ENVIRONMENTAL Operating Temperature Range 32° to 122°F (0° to 50°C) Storage Temperature Range -4° to 185°F (-20° to 85°C) Relative Humidity 25% ~ 85% RH Power Provided to Connected Device(s) 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Cable Length (cm)	150	
Operating Temperature Range 32° to 122°F (0° to 50°C) Storage Temperature Range -4° to 185°F (-20° to 85°C) Relative Humidity 25% ~ 85% RH Power Provided to Connected Device(s) 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000	
Storage Temperature Range -4° to 185°F (-20° to 85°C) Relative Humidity 25% ~ 85% RH Power Provided to Connected Device(s) 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	ENVIRONMENTAL		
Relative Humidity 25% ~ 85% RH Power Provided to Connected b4 (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Operating Temperature Range	32° to 122°F (0° to 50°C)	
Power Provided to Connected Device(s) 5A (100W) Power Delivery CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Storage Temperature Range	-4° to 185°F (-20° to 85°C)	
CONNECTIONS Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Relative Humidity	25% ~ 85% RH	
Side A - Connector 1 THUNDERBOLT 3 (Type-C MALE) Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Power Provided to Connected Device(s)	5A (100W) Power Delivery	
Side B - Connector 1 THUNDERBOLT 3 (Type-C MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	CONNECTIONS		
Connector Plating Nickel FEATURES & SPECIFICATIONS Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Side A - Connector 1	THUNDERBOLT 3 (Type-C MALE)	
Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Side B - Connector 1	THUNDERBOLT 3 (Type-C MALE)	
Data Transfer Rate 20 Gbps High Voltage No Locking Plug No Displayport Specification 1.2	Connector Plating	Nickel	
High Voltage No Locking Plug No Displayport Specification 1.2	FEATURES & SPECIFICATIONS		
Locking Plug No Displayport Specification 1.2	Data Transfer Rate	20 Gbps	
Displayport Specification 1.2	High Voltage	No	
	Locking Plug	No	
STANDARDS & COMPLIANCE	Displayport Specification	1.2	
	STANDARDS & COMPLIANCE		
Product Certifications UL Listed	Product Certifications	UL Listed	





Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.