

TP-Link Omada Pro S6500-24GP4XF network switch Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Grey

Brand: TP-Link Product family: Omada Pro Product code: S6500-24GP4XF

Product name : S6500-24GP4XF

- 24× Gigabit PoE+ RJ45 ports and 4× 10 Gbps SFP+ slots
- Up to 720 W total PoE budget*
- Physical stacking for built-in redundancy and performance
- L3 Features: OSPF, BGP, IS-IS, VRRP, PIM-SM/PIM-DM/PIM-SSM, ECMP, PBR
- Security Strategies: MACsec, Secure Boot, RADSEC, IMPB, SFTP, 802.1X
- Highly available with two field-replaceable power supplies,** VRRP, ERPS, and BFD
- Easy O&M: NETCONF, Configuration Rollback, Hot Patching, and RSPAN
- Centralized cloud management via the web or the Omada app

Omada Pro 24-Port Gigabit Stackable L3 Managed PoE+ Switch with 4 10G Slots



Management features		Security	
Switch type * Switch layer Quality of Service (QoS) support Web-based management Cloud-managed Configuring Location Settings (CLI)	Managed L3 ✓	MAC address filtering Static port security SSH/SSL support Loop protection Password protection Authentication type	✓ ✓ ✓ AAA, RADIUS, TACACS+
System event log	/	Multicast features	
Ports & interfaces		Multicast support	✓
Basic switching RJ-45 Ethernet ports quantity *	24	Design	
Basic switching RJ-45 Ethernet ports type * SFP+ module slots quantity Console port USB 2.0 ports quantity	Gigabit Ethernet (10/100/1000) 4 RJ-45/USB Type-C 2	Rack mounting * Stackable * Form factor Product colour Number of fans	✓ ✓ 1U Grey 4 fan(s)
Network		Power	+ ran(3)
Networking standards * 10G support * Port mirroring Flow control support Link aggregation	IEEE 802.1p, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az Power supply inc AC input voltage AC input frequer Power consumpt Power over Eth Power over Ethe	Power source * Power supply included * AC input voltage AC input frequency Power consumption (max)	AC 100 - 240 V 50/60 Hz 916.6 W
Broadcast storm control		Power over Ethernet (PoE)	
Rate limiting		Power over Ethernet (PoE) *	✓
Spanning tree protocol	✓	Power over Ethernet (PoE) ports quantity	24
Active link detection	*	Total Power over Ethernet (PoE) budget	720 W

Network		Operational conditions	
Virtual LAN features	MAC address-based VLAN, Protocol- based VLAN, Voice VLAN	Operating temperature (T-T) Storage temperature (T-T)	-5 - 40 °C -40 - 70 °C
Data transmission		Operating relative humidity (H-H)	10 - 90%
Switching capacity * Forwarding rate	128 Gbit/s 95.2 Mpps	Storage relative humidity (H-H) Heat dissipation	5 - 90% 3125.6 BTU/h
MAC address table *	32000 entries	Weight & dimensions	
Number of queues	8	Width	440 mm
Static route	✓	Depth	420 mm
Jumbo frames support	✓	Height	44 mm
Jumbo frames	9000	Packaging content	
Packet buffer memory	3 MB	Cables included	AC
Security		Quick start guide	✓
DHCP features	DHCP relay, DHCP server, DHCPv6 relay	Rack mount kit	✓
Access Control List (ACL)	✓		
IGMP snooping	1		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.