



TP-Link Omada Pro S7500-24Y4C network switch Managed L3 Grey

Brand : TP-Link

Product family: Omada Pro

Product code: S7500-24Y4C

Product name : S7500-24Y4C

- 24× 25 Gbps SFP28 slots and 4× 100 Gbps QSFP28 slots
- Physical stacking for built-in redundancy and performance
- L3 Features: OSPF, BGP, IS-IS, VRRP, PIM-SM/PIM-DM/PIM-SSM, ECMP, PBR
- Security Strategies: Secure Boot, RADSEC, IMPB, SFTP, 802.1X, Port Security
- Highly available with two field-replaceable power supplies,* VRRP, ERPS, BFD
- Easy O&M: NETCONF, Configuration Rollback, Hot Patching, and RSPAN
- Centralized cloud management via the web or the Omada app

Omada Pro 24-Port 25G Stackable L3 Managed Aggregation/Core Switch with 4 100G Slots

TP-Link Omada Pro S7500-24Y4C. Switch type: Managed, Switch layer: L3. Console port: RJ-45/USB Type-C. MAC address table: 128000 entries, Switching capacity: 2000 Gbit/s. Networking standards: IEEE 802.1p. Rack mounting



Management features		Security	
Switch type *	Managed	MAC address filtering	✓
Switch layer	L3	Static port security	✓
Cloud-managed	✓	SSH/SSL support	✓
Configuring Location Settings (CLI)	✓	Authentication type	AAA, RADIUS, TACACS+
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports type *	✗	Rack mounting *	✓
Console port	RJ-45/USB Type-C	Stackable *	✓
QSFP28 ports quantity	4	Product colour	Grey
SFP28 ports quantity	24	LED indicators	✓
Network		Number of fans	4 fan(s)
		Power	
	Networking standards *	Power source *	AC
	10G support *	Power supply included *	✓
	Flow control support	AC input voltage	100 - 240 V
	Link aggregation	AC input frequency	50/60 Hz
	Broadcast storm control	Power consumption (max)	137.63 W
Virtual LAN features	Rate limiting	Power over Ethernet (PoE)	
	Spanning tree protocol	Power over Ethernet (PoE) *	✗
	IP subnet-based VLAN, MAC address-based VLAN, Port-based VLAN, Protocol-based VLAN, Voice VLAN	Operational conditions	
Data transmission		Operating temperature (T-T)	-5 - 40 °C
Switching capacity *	2000 Gbit/s	Storage temperature (T-T)	-40 - 70 °C
Forwarding rate	810 Mpps	Operating relative humidity (H-H)	10 - 90%
MAC address table *	128000 entries	Storage relative humidity (H-H)	5 - 90%
Number of queues	8	Heat dissipation	1658.78 BTU/h

Data transmission		Weight & dimensions	
Static route	✓	Width	440 mm
Jumbo frames support	✓	Depth	380 mm
Jumbo frames	9000	Height	44 mm
Packet buffer memory	8 MB	Packaging content	
Security		Cables included	AC, LAN (RJ-45)
DHCP features	DHCP relay, DHCP server	Quick start guide	✓
Access Control List (ACL)	✓		
IGMP snooping	✓		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.