



APC BR1350MS uninterruptible power supply (UPS) Line-Interactive 1.35 kVA 810 W 10 AC outlet(s)

Brand : APC

Product code: BR1350MS

Product name : BR1350MS



- Alarm notification
- Audible alarms
- Automatic self-test
- Battery replacement without tools
- Boost and Trim Automatic Voltage Regulation (AVR)
- Building Wiring Fault Indicator
- Catastrophic Event Protection
- EMI and RFI noise filtering
- Dataline surge protection
- ENERGY STAR for UPS
- Hot-swappable batteries
- LCD graphics display
- Lifetime data recovery warranty
- PowerChute Personal Edition OS Compatibility
- RoHS
- Sine wave output
- USB charging ports

810 W, 120V, 60Hz, 10x NEMA 5-15R, USB, LCD, 260x100x368 mm

APC BR1350MS uninterruptible power supply (UPS) Line-Interactive 1.35 kVA 810 W 10 AC outlet(s):

High Performance Computer and Electronics UPS for Premium Power Protection
APC BR1350MS. UPS topology: Line-Interactive, Output power capacity: 1.35 kVA, Output power: 810 W.
AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 10 AC outlet(s). Battery
technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 16 h. Form
factor: Tower, Product colour: Black, Cable length: 1.83 m. Certification: FCC 15 B, NOM, TUV C-US



Features		Design	
UPS topology *	Line-Interactive	Cable length	1.83 m
Output power capacity *	1.35 kVA	Product colour *	Black
Output power *	810 W	Display type	LCD
Waveform *	Sine	Operational conditions	
Input operation voltage (min) *	88 V	Operating temperature (T-T)	0 - 40 °C
Input operation voltage (max) *	147 V	Storage temperature (T-T)	-15 - 45 °C
Input frequency *	60 Hz	Operating relative humidity (H-H)	0 - 95%
Output frequency	60 Hz	Storage relative humidity (H-H)	0 - 95%
Automatic Voltage Regulation (AVR)	✓	Operating altitude	0 - 3000 m
Maximum current	12 A	Non-operating altitude	0 - 3000 m
Surge energy rating	1080 J	Certificates	
Hold time (min)	8 ms	Certification	FCC 15 B, NOM, TUV C-US
Hold time (max)	10 ms	Packaging content	
EMI/RFI noise filtering	✓	Cables included	USB cable
Noise level	45 dB	Manual	✓
Surge protection	✓	Sustainability	
Surge protection features	Coax, Network	Sustainability certificates	ENERGY STAR
Audible alarm(s)	✓	Weight & dimensions	
Audible alarm modes	Low battery alarm, Overload alarm	Width	100 mm
Ports & interfaces		Depth	368 mm
AC outlet types	NEMA 5-15R	Height	260 mm
Power plug	NEMA 5-15P		
AC outlets quantity	10 AC outlet(s)		

Ports & interfaces		Weight & dimensions	
USB port	✓	Weight	11.7 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package width	223 mm
Battery life (max)	5 year(s)	Package depth	482 mm
Battery recharge time	16 h	Package height	358 mm
Hot-swap battery	✓	Package weight	13.3 kg
Automatic battery test	✓	Logistics data	
Cold start	✓	Products per pallet	16 pc(s)
Design		Master (outer) case gross weight	13.3 kg
Form factor *	Tower	Products per master (outer) case	1 pc(s)
		Other features	
		Output voltage	120 V



0731304335399



731304335399

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.