

APC SMC1000-2UC uninterruptible power supply (UPS) Line-Interactive 1 kVA 600 W

Brand : APC Product code: SMC1000-2UC

Product name: SMC1000-2UC



- APC Smart-UPS C 1000VA LCD RM 2U 120V with SmartConnect
- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices
- Includes: Documentation CD, Installation guide, Rack mounting brackets, USB cable APC Smart-UPS C, 1000VA, LCD, RM, 2U, 120V, with SmartConnect

APC SMC1000-2UC. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 600 W. Battery life (max): 6 year(s), Battery recharge time: 3 h. Product colour: Black, Display type: LCD. Compliance certificates: RoHS, Certification: CSA C22.2 No 107.1, CULus, ENERGY STAR V2.0 (USA), FCC part 15 class A, ICES-003, UL 1778. Cables included: USB cable



Features		Design			
UPS topology *	Line-Interactive	Product colour *	Black		
Output power capacity *	1 kVA	Display type	LCD		
Output power *	600 W	Operational conditions			
Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max)	50/60 Hz 110 V	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 40 °C 0 - 95% 0 - 3048 m 0 - 15240 m		
Output frequency		Certificates			
Automatic Voltage Regulation (AVR)	✓	Compliance certificates	RoHS		
Surge energy rating Response time Noise level	680 J 10 ms 41 dB	Certification	CSA C22.2 No 107.1, CULus, ENERGY STAR V2.0 (USA), FCC part 15 class A, ICES-003, UL 1778		
Audible alarm(s)	√	Packaging content			
Audible alarm modes	Alarm when on battery, Low battery alarm	Rack mount kit Cables included	✓ USB cable		
Ports & interfaces		Sustainability			
USB port	✓	Sustainability certificates	ENERGY STAR		
Ethernet LAN (RJ-45) ports	1	Weight & dimensions			
Battery Battery life (max) 6 year(s) Battery recharge time 3 h Hot-swap battery	3 h	Width Depth Height Weight	432 mm 406 mm 86 mm 20.5 kg		
Cold start	✓	Packaging data			
		Package width Package depth	535 mm 570 mm		

Pac			

Package height 235 mm Package weight 20.7 kg

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.