

APC SMX1500RM2UC uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 1200 W 8 AC outlet(s)

Brand: APC Product code: SMX1500RM2UC

Product name: SMX1500RM2UC



1.44 kVA, 1.2 kW, 120V, 50/60Hz, 645J, 40dB, 432x490x89mm, 24.82kg, Black APC SMX1500RM2UC. UPS topology: Line-Interactive, Output power capacity: 1.44 kVA, Output power: 1200 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: cUL Listed, TAA compliance, UL 1778



Features		Battery	
JPS topology * Line-Interactive Output power capacity * 1.44 kVA Output power * 1200 W Naveform * Sine nput operation voltage (min) * 75 V	Number of batteries supported Battery life (max) Battery recharge time Hot-swap battery Automatic battery test	1 5 year(s) 3 h ✓	
Input operation voltage (max) * Input frequency * Output operation voltage (max) Output frequency Automatic Voltage Regulation (AVR) Maximum current Surge energy rating	154 V 50/60 Hz 120 V 50/60 Hz R) ✓ 12 A 645 J	Pesign Form factor * Rack capacity Cable length Product colour * Display type LED indicators	Rackmount/Tower 2U 2.44 m Black LCD
Emergency Power Off (EPO) Output voltage Total Harmonic Distortion (THD) Noise level Power protection features Audible alarm(s) Audible alarm modes	5% 40 dB Short circuit Alarm when on battery, Low battery alarm, Overload alarm	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Auto-restart Ports & interfaces AC outlet types Power plug	NEMA 5-15R NEMA 5-15P	Certificates Compliance certificates Certification	RoHS cUL Listed, TAA compliance, UL 1778
AC outlets quantity USB port USB 2.0 ports quantity USB port type	8 AC outlet(s) 1 USB Type-B	Sustainability Sustainability certificates	ENERGY STAR

Ports & interfaces		Weight & dimensions	
Serial interface	✓	Width	432 mm
Serial interface type	RS-232	Depth	490 mm
SmartSlot	✓	Height	89 mm
Pattom.		Weight	24.8 kg
Battery Control to the delegation of the control o		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package width	589 mm
		Package depth	620 mm
		Package height	246 mm
		Package weight	30 kg
		Logistics data	
		Harmonized System (HS) code	85078000





731304401131

0731304401131

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.