

## APC Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA



Brand : APC Product code: SMT1500RMI2UNC


Product name: Smart-UPS SMT1500RMI2UNC - 4x C13,

USB, rack mountable, NMC, 1500VA

APC Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA APC Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 1000 W. AC outlet types: C13 coupler, C14 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 432 Ah, Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE

Features		Design	
UPS topology * Line-Interactive Output power capacity * 1.5 kVA Output power * 1000 W Waveform * Sine Input operation voltage (min) * 151 V Input operation voltage (max) * 302 V Input frequency * 50/60 Hz Output operation voltage (min) 220 V Output operation voltage (max) 240 V Output frequency 50/60 Hz Output requency 50/60 Hz Output voltage regulation 5% Surge energy rating 459 J	Product colour * Display type LED indicators	Black LCD ✓	
		Operational conditions	
	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m	
	459 J	Certificates	
Response time Emergency Power Off (EPO) Noise level Audible alarm(s)	2 ms O 46 dB ✓	Compliance certificates Certification	RoHS CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Web-based management	· ·	Packaging content	
Audible alarm modes Auto-restart	Battery replacement	Rack mount kit Cables included	✓ Input power cable, USB cable
Ports & interfaces		Quick installation guide	✓
AC outlet types C13 coupler, C14 Power plug C14 coupler AC outlets quantity 4 AC outlet(s)	C13 coupler, C14 coupler C14 coupler	<b>Sustainability</b> Sustainability certificates	Green Premium
	4 AC outlet(s) 1	Weight & dimensions	
Ethernet LAN (RJ-45) ports	1	Width	432 mm 457 mm
Battery		Depth Height	457 mm
Battery technology	Sealed Lead Acid (VRLA)	Weight	28.6 kg
Battery capacity	432 Ah	Packaging data	
Battery recharge time	3 h	Resource CD	✓
Hot-swap battery	<b>V</b>	Package width	594 mm
Automatic battery test Cold start	1	Package depth	603 mm
Design	<b>,</b>	Package height  Package weight	251 mm 31.8 kg
Form factor *	Rackmount	Logistics data	3
Rack capacity	2U	Products per pallet Harmonized System (HS) code Total carbon footprint (kg of CO2e)	8 pc(s) 85078000 1407.66

Other features	
Output voltage	230 V





731304327684

0731304327684

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.