ASUS ProArt PA27UCGE computer monitor 68.6 cm (27") 3840 x 2160 pixels 4K Ultra HD LED Black



Brand : ASUS

Product family: ProArt

Product code: 90LM04NC-B01K71

Product name : PA27UCGE

ProArt Display PA27UCGE Professional 4K Monitor (27 inch, 3840 x 2160 IPS panel, 160Hz, HDR-10, 600 nits, 98% DCI-P3, Delta E<1 color accuracy, Light Sync, USB-C, DisplayPort, HDMI)
ASUS ProArt PA27UCGE. Display diagonal: 68.6 cm (27"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 1 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black

5 YIL GARANTİ UZATMA ÜRÜN KAYIT SAYFASI

*Ürününüzü kaydetmek için QR kodu okutunuz.

Display	
Display diagonal *	68.6 cm (27")
Display resolution *	3840 x 2160 pixels
HD type *	4K Ultra HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
LED backlight	✔
Touchscreen *	✘
Display brightness (peak)	600 cd/m²
Display brightness (typical)	600 cd/m²
Response time *	1 ms
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	✔
Screen shape *	Flat
Contrast ratio (typical) *	1000:1
Maximum refresh rate *	160 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	1.073 billion colours
Pixel pitch	0.155 x 0.155 mm
Pixel density	163 ppi
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Digital horizontal frequency	31 - 255 kHz
Digital vertical frequency	48 - 160 Hz
High Dynamic Range (HDR) supported	✔
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10), Hybrid Log-Gamma Pro (HLG Pro)

Ports & interfaces	
DisplayPort version	1.4
Headphone out *	✔
Headphone outputs	1
Headphone connectivity	3.5 mm
Built-in KVM switch	✔
HDCP	✔
HDCP version	2.3

Ergonomics	
VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Wall mountable	✔
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Adjustable height (max)	12 cm
Pivot	✔
Pivot angle	-90 - 90°
Swivelling	✔
Swivel angle range	-30 - 30°
Tilt adjustment	✔
Tilt angle range	-5 - 23°
Picture-in-Picture	✔
On Screen Display (OSD)	✔

Power	
Energy efficiency class (SDR) *	F
Energy efficiency class (HDR) *	G

Display	
Colour depth	10 bit
Colour gamut standard	DCI-P3, sRGB
sRGB coverage (typical)	100%
DCI-P3 coverage	98%

Performance	
NVIDIA G-SYNC *	✗
AMD FreeSync *	✗
VESA Adaptive Sync support	✓
Flicker-free technology	✓
Low Blue Light technology	✓

Multimedia	
Number of speakers	2
RMS rated power	4 W
Built-in speaker(s) *	✓
Built-in camera *	✗

Design	
Market positioning *	Graphics design
Product colour *	Black
Detachable stand	✓
Feet colour	Black

Ports & interfaces	
Built-in USB hub *	✓
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB Type-A downstream ports quantity	2
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	✓
USB Power Delivery (USB PD)	✓
USB Power Delivery up to	96 W
HDMI *	✓
HDMI ports quantity	2
HDMI version	2.1
DisplayPorts quantity	1

Power	
Energy consumption (SDR) per 1000 hours *	26 kWh
Energy consumption (HDR) per 1000 hours *	66 kWh
Power consumption (typical) *	27 W
Power consumption (standby) *	0.4 W
Power consumption (off)	0.3 W
Power consumption (PowerSave)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Weight & dimensions	
Width (with stand)	612.4 mm
Depth (with stand)	201.8 mm
Height (with stand)	574.7 mm
Weight (with stand)	6.4 kg
Width (without stand)	612.4 mm
Depth (without stand)	47.6 mm
Height (without stand)	380.8 mm
Weight (without stand)	4.5 kg

Packaging data	
Package width	780 mm
Package depth	140 mm
Package height	492 mm
Package weight	10.6 kg
Package type	Box

Packaging content	
Stand included	✓

Sustainability	
Sustainability certificates	ENERGY STAR, EPEAT Gold, Forest Stewardship Council (FSC) Mix

Other features	
Certification	Energy Star EPEAT Gold TÜV Flicker-free TÜV Low Blue Light VESA DisplayHDR 600 Calman Ready FSC MIX Mac Compliance

Technical details	
Native refresh rate	60 Hz

4711387734667

0197105788701

197105788701

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 31-OCT-2026. Prints or copies of Information are only valid on the printed Publication date