



# APC SMX1500RM2UCNC uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 1350 W 8 AC outlet(s)

Brand : APC

Product code: SMX1500RM2UCNC

Product name : SMX1500RM2UCNC



Smart-UPS X 1500, 1440VA, 120V, LCD, rackmount, 2U, 8x NEMA 5-15R outlets, w/SmartConnect port and network card

APC SMX1500RM2UCNC uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 1350 W 8 AC outlet(s):

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Includes: Cat 5 Ethernet cable, Installation guide, Rack mounting hardware, Rack mounting support rails, Removable support feet, Smart UPS signalling RS-232 cable, USB cable

APC SMX1500RM2UCNC. UPS topology: Line-Interactive, Output power capacity: 1.44 kVA, Output power: 1350 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 8 AC outlet(s).

Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 48 V, Battery life (max): 5 year(s). Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: cUL Listed, TAA compliance, UL 1778



Features		Battery	
UPS topology *	Line-Interactive	Battery voltage	48 V
Output power capacity *	1.44 kVA	Number of batteries supported	1
Output power *	1350 W	Battery life (max)	5 year(s)
Waveform *	Sine	Battery recharge time	3 h
Input operation voltage (min) *	75 V	Hot-swap battery	✓
Input operation voltage (max) *	154 V	Automatic battery test	✓
Input frequency *	50/60 Hz		
Output operation voltage (max)	120 V	Design	
Output frequency	50/60 Hz	Form factor *	Rackmount/Tower
Automatic Voltage Regulation (AVR)	✓	Rack capacity	2U
Maximum current	12 A	Cable length	2.44 m
Surge energy rating	600 J	Product colour *	Black
Emergency Power Off (EPO)	✓	Display type	LCD
Output voltage Total Harmonic Distortion (THD)	5%	LED indicators	✓
Noise level	40 dB	Operational conditions	
Power protection features	Over current	Operating temperature (T-T)	0 - 40 °C
Audible alarm(s)	✓	Storage temperature (T-T)	-15 - 45 °C
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Operating relative humidity (H-H)	0 - 95%
Auto-restart	✓	Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
Ports & interfaces		Certificates	
AC outlet types	NEMA 5-15R	Compliance certificates	RoHS
Power plug	NEMA 5-15P	Certification	cUL Listed, TAA compliance, UL 1778
AC outlets quantity	8 AC outlet(s)		
USB port	✓	Sustainability	
USB 2.0 ports quantity	1	Sustainability certificates	ENERGY STAR
USB port type	USB Type-B		

Ports & interfaces		Weight & dimensions	
Serial interface	✓	Width	432 mm
Serial interface type	RS-232	Depth	490 mm
Ethernet LAN (RJ-45) ports	1	Height	89 mm
SmartSlot	✓	Weight	24.8 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package width	589 mm
		Package depth	620 mm
		Package height	246 mm
		Package weight	30 kg



0731304401148



731304401148

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.