**EPSON**

# Epson DS-730N Sheet-fed scanner 600 x 600 DPI A4 Black, Grey

**Brand :** Epson

**Product name :** DS-730N

**Product code:** B11B259201

215.9 mm x 6096 mm, A4, CIS, 27 - 413 g/m², LAN, USB 2.0 Type B, 3.6 kg
Epson DS-730N. Maximum scan size: 215.9 x 6096 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 30 bit. Scanner type: Sheet-fed scanner, Product colour: Black, Grey, Display: LCD. Sensor type: CIS, Daily duty cycle (max): 4500 pages, Light source: ReadyScan LED. Auto document feeder (ADF) input capacity: 100 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Plastic Card, Post Card(JPN), ISO A-series sizes (A0...A9): A4, A5, A6

## Scanning

| | |
|---|---|
| Maximum scan size * | 215.9 x 6096 mm |
| Optical scanning resolution * | 600 x 600 DPI |
| Colour scanning | ✔ |
| Duplex scanning * | ✔ |
| Input colour depth | 30 bit |
| Output colour depth | 24 bit |
| Input greyscale depth | 10 bit |
| Output greyscale depth | 8 bit |
| Output monochrome depth | 8 bit |
| ADF scan speed (b/w, A4) | 40 ppm |
| ADF scan speed (colour, A4) | 40 ppm |
| Black/white scanning colour modes | Monochrome |

## Design

| | |
|---|---|
| Scanner type * | Sheet-fed scanner |
| Product colour * | Black, Grey |
| Display | LCD |
| Display diagonal | 3.81 cm (1.5") |
| Colour display | ✔ |
| Built-in display * | ✔ |

## Performance

| | |
|---|---|
| Sensor type * | CIS |
| Light source | ReadyScan LED |
| Scan file formats | JPEG, PDF, TIFF |
| Daily duty cycle (max) * | 4500 pages |
| Scan to | E-mail, FTP, Network folder |
| Password protection | ✔ |
| Ultrasonic sensor | ✔ |

## Input capacity

| | |
|---|---|
| Auto document feeder (ADF) input capacity | 100 sheets |

## Paper handling

| | |
|---|---|
| Scanning media types supported | Business Card, Plastic Card, Post Card(JPN) |

## Ports & interfaces

| | |
|---|---|
| USB port * | ✔ |
| USB version | 2.0 |
| USB connector type | USB Type-B |

## Network

| | |
|---|---|
| Ethernet LAN | ✔ |
| IPv6 support | ✔ |

## Power

| | |
|---|---|
| Power supply type * | AC |
| Power consumption (typical) | 14 W |
| Power consumption (off) | 0.1 W |
| AC input frequency | 50 - 60 Hz |
| Sleep mode | ✔ |
| Input voltage | 100 - 240 V |
| Power consumption (sleep) | 1.5 W |

## Weight & dimensions

| | |
|---|---|
| Width | 296 mm |
| Depth | 169 mm |
| Height | 167 mm |
| Weight | 3.6 kg |

## Packaging data

| | |
|---|---|
| Quantity per pack | 1 pc(s) |
| Package width | 270 mm |
| Package depth | 370 mm |
| Package height | 320 mm |
| Package weight | 4.93 kg |

## Packaging content

| | |
|---|---|
| Cables included | AC |

## Operational conditions

| | |
|---|---|
| Operating temperature (T-T) | 5 - 35 °C |
| Storage temperature (T-T) | 25 - 60 °C |
| Operating relative humidity (H-H) | 15 - 80% |
| Storage relative humidity (H-H) | 15 - 85% |

## Paper handling

| | |
|---|---|
| Maximum ISO A-series paper size * | A4 |
| ISO A-series sizes (A0...A9) | A4, A5, A6 |
| ISO B-series sizes (B0...B9) | B4, B5, B6 |
| Letter | ✔ |
| Legal | ✔ |
| Auto Document Feeder (ADF) media weight | 27 - 413 g/m² |

## Other features

| | |
|---|---|
| Output resolutions | 75, 100, 150, 200, 240, 300, 600, 1200 dpi |
| Image formats supported | BMP, JPEG, TIFF, PNG |
| Cabling technology | 10/100/1000Base-T(X) |

## Logistics data

| | |
|---|---|
| Products per pallet | 48 pc(s) |
| Country of origin | Indonesia |
| Pallet gross weight | 0 g |
| Products per pallet (UK) | 60 pc(s) |
| Pallet weight (UK) | 0 g |

0010343953529

010343953529

**Catalog Object Cloud**