GIGABYTE

## GIGABYTE R183 Intel C741 LGA 4677 (Socket E) Rack (1U)

Brand : GIGABYTE

Product name : R183

Product code: R183-Z93-AAD1



- 2 x OCP 3.0 Gen5 x16 slots
- 1+1 1600W 80 PLUS Platinum redundant power supplies
- Dual Intel® Xeon® CPU Max Series
- 8-Channel DDR5 RDIMM, 32 x DIMMs
- Dual ROM Architecture
- 1u, DIMM x32, DDR5, 8-channel, RDIMM

GIGABYTE R183. Motherboard chipset: Intel C741, Processor socket: LGA 4677 (Socket E), Processor manufacturer: Intel. Supported memory types: DDR4-SDRAM, Supported DIMM module capacities: 16GB, 32GB, 64GB, 128GB, Supported RDIMM clock speeds: 2933,3200 MHz. Storage drive sizes supported: 2.5,3.5,M.2. On-board graphics card model: Aspeed AST2500. Ethernet interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, LAN controller: Intel® I350-AM2



Processor		Features	
Built-in processor *	×	Trusted Platform Module (TPM)	1
Motherboard chipset * Processor socket *	Intel C741 LGA 4677 (Socket E)	Trusted Platform Module (TPM) version	2.0
Processor manufacturer	Intel	Backplanes support	1
Processor family Processor generation Number of processors supported *	Intel® Xeon® Intel Xeon Scalable 4th Gen 2	Logistics data	
		Harmonized System (HS) code	84714100
		Design	
Memory		Chassis type *	Rack (1U)
Number of DIMM slots * Supported memory types * Supported DIMM module capacities	32 DDR4-SDRAM 16GB 32GB 64GB 128GB	LED indicators	HDD, LAN, Status
		Power	
Supported RDIMM module capacities	2933,3200 MHz	Power supply *	1600 W
Memory channels	Octa-channel	Number of main power supplies	2
Storage		Redundant power supply (RPS) support	<ul> <li>Image: A second s</li></ul>
Number of storage drives supported *	4	Number of redundant power supplies supported	1
Hot-swap HDD bays *	1	AC input voltage	100 - 240 V
Number of 2.5" bays	4	DC output current (+12 V)	97 A
Number of 3.5" bays	4	Operational conditions	
Storage drive sizes supported	2.5,3.5,M.2	Operating temperature (T-T)	10 - 35 °C
Graphics		Storage temperature (T-T)	-40 - 60 °C
Discrete graphics card model	Not available	Operating relative humidity (H-H)	8 - 80%
On-board graphics card model	Aspeed AST2500	Storage relative humidity (H-H)	20 - 95%
Network		Weight & dimensions	
Ethernet LAN	1	Height	730 mm
Ethernet interface type	Gigabit Ethernet	Weight	21.9 kg
Ethernet LAN data rates	10,100,1000 Mbit/s	Packaging data	
LAN controller	Intel® I350-AM2		1 x R183-S90-AAD2 2 x CPU
Ports & interfaces Ethernet LAN (RJ-45) ports *	2	Packaging content	heatsinks 1 x Mini-DP to D-Sub cable 6 x Carriers 1 x 2-Section Rail kit
VGA (D-Sub) ports quantity	1	Package width	1045 mm
COM ports quantity	1	Package depth	595 mm
Expansion slots		Package height	249 mm
PCI Express slots version	4.0	Package weight	24.5 kg
PCI Express x16 slots	4		
Number of M.2 (M) slots	3		

**Catalog Object Cloud** 



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.