Lenovo.

Lenovo ThinkPad X1 2-in-1 Gen 9 Intel Core Ultra 7 165U Hybrid (2-in-1) 35.6 cm (14") Touchscreen WUXGA 32 GB LPDDR5x-SDRAM 1 TB SSD Wi-Fi 6E (802.11ax) Windows 11 Pro Arabic Grey

Brand : Lenovo Product family: ThinkPad Product code: 21KE005SUS

Product name: ThinkPad X1 2-

in-1 Gen 9

- Windows 11 Pro
- Intel Core Ultra 7 165U (12MB Cache)
- 35.6 cm (14") WUXGA 1920 x 1200 IPS Touch
- 32GB (6400MHz) LPDDR5x-SDRAM & 1000GB SSD

Intel Core Ultra 7 165U (12MB Cache), 32GB LPDDR5x-SDRAM, 1000GB SSD, 35.6 cm (14") WUXGA 1920 x 1200 IPS Touch, Intel Graphics, WLAN, Webcam, Windows 11 Pro

Lenovo ThinkPad X1 2-in-1 Gen 9. Product type: Hybrid (2-in-1), Form factor: Convertible (Folder). Processor family: Intel Core Ultra 7, Processor model: 165U. Display diagonal: 35.6 cm (14"), HD type: WUXGA, Display resolution: 1920 x 1200 pixels, Touchscreen. Internal memory: 32 GB, Internal memory type: LPDDR5x-SDRAM. Total storage capacity: 1 TB, Storage media: SSD. On-board graphics card model: Intel Graphics. Operating system installed: Windows 11 Pro. Product colour: Grey





Design		Camera	
Product type * Product colour * Form factor * Housing material	Hybrid (2-in-1) Grey Convertible (Folder) Aluminium	Front camera Front camera resolution Front camera HD type Infrared (IR) camera	✓ 1920 x 1080 pixels Full HD ✓
Display		Privacy camera	✓
Display diagonal * Display resolution *	35.6 cm (14") 1920 x 1200 pixels	Privacy type Network	Privacy shutter
Touchscreen * HD type Panel type LED backlight Native aspect ratio Anti-reflective coating Anti-smudge coating Display brightness RGB colour space Colour gamut Maximum refresh rate Contrast ratio (typical)	₩UXGA IPS 16:10 400 cd/m² \$RGB 100% 60 Hz 1000:1	Top Wi-Fi standard * Wi-Fi standards Mobile network connection * Antenna type WLAN controller model WLAN controller manufacturer Ethernet LAN Bluetooth Bluetooth version Near Field Communication (NFC) WWAN	Wi-Fi 6E (802.11ax) Wi-Fi 6E (802.11ax) X 2x2 Intel Wi-Fi 6E AX211 Intel X ✓ 5.3 X Not installed
Processor	2000.2	Ports & interfaces	
Processor manufacturer * Processor family * Processor generation Processor model * Processor cores Processor threads Processor boost frequency	Intel Intel Core Ultra 7 Intel® Core™ Ultra (Series 1) 165U 12 14 4.9 GHz	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI version Thunderbolt 4 ports quantity Intel® Thunderbolt 4 Combo headphone/mic port	2 1 2.1 2

Processor		Ports & interfaces	
Performance cores	2	USB Type-C DisplayPort Alternate	√
Efficient cores	8	Mode	
Low Power Efficient-cores	2	USB Sleep-and-Charge	
Performance-core Max Turbo Frequency	4.9 GHz	USB Sleep-and-Charge ports	1
Efficient-core Max Turbo Frequency	3.8 GHz	Performance	
Low Power Efficient-core Max Turbo		Motherboard chipset	Intel SoC
Frequency	2.1 GHz	Keyboard	
Performance-core base frequency	1.7 GHz	Pointing device	ThinkPad UltraNav
Efficient-core base frequency	1.2 GHz	Numeric keypad *	×
Low Power Efficient-core Base Frequency	700 MHz	Keyboard backlit	✓
Processor cache	12 MB	Spill-resistant keyboard	/
Processor cache type	Smart Cache	Keyboard language	Arabic
Processor base power	15 W	. 5 5	7.1.42.10
Maximum turbo power	57 W	Software	
Neural processor unit (NPU)		Operating system language	Arabic, English
Neural processor unit (NPU)	Intel Al Boost	Operating system installed *	Windows 11 Pro
Sparsity support	/	Bundled software	Intel Connectivity Performance Suite
Windows Studio effects support	*	Battery	
Al software frameworks supported	DirectML, ONNX RT, OpenVINO,	Battery technology	Lithium Polymer (LiPo)
by NPU	Windows ML	Battery capacity *	57 Wh
Memory		Fast charging	√ WII
Internal memory *	22 CB	5 5	•
Internal memory type	32 GB LPDDR5x-SDRAM	Power	
Memory clock speed	6400 MHz	AC adapter power	65 W
Memory form factor	On-board	AC adapter frequency	50 - 60 Hz
Maximum internal memory *	32 GB	AC adapter input voltage	100 - 240 V
Memory channels	Octa-channel	USB Type-C charging port *	•
Storage		USB Power Delivery (USB PD)	√
Total storage capacity *	1 TR	Security	
Total storage capacity * Storage media *	1 TB SSD	Security Cable lock slot	✓
Total storage capacity * Storage media * Total SSDs capacity	1 TB SSD 1 TB		✓ Kensington
Storage media *	SSD	Cable lock slot	
Storage media * Total SSDs capacity	SSD 1 TB	Cable lock slot Cable lock slot type	Kensington
Storage media * Total SSDs capacity Number of SSDs installed	SSD 1 TB 1	Cable lock slot Cable lock slot type Fingerprint reader	Kensington ✓
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity	SSD 1 TB 1 1 TB	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello	Kensington ✓ ×
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface	SSD 1 TB 1 1 TB	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM)	Kensington ✓ × ✓
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe	SSD 1 TB 1 1 TB PCI Express 4.0	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello	Kensington ✓ ×
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM)	Kensington ✓ × ✓
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 2280 (22 x 80 mm)	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	Kensington ✓ X ✓ ✓ 2.0
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type *	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 2280 (22 x 80 mm) ×	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection	Kensington ✓ × ✓ 2.0
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 2280 (22 x 80 mm) ×	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type	Kensington ✓ × ✓ 2.0
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model *	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 2280 (22 x 80 mm) ×	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 2280 (22 x 80 mm) X X	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T)	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 2280 (22 x 80 mm) × ×	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T)	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card *	SSD 1 TB 1 1 TB PCI Express 4.0 M.2 2280 (22 x 80 mm) X Not available Intel	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95%
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board GPU manufacturer Discrete graphics card *	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 2280 (22 x 80 mm) × × Not available ✓ Intel X	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95%
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board GPU manufacturer Discrete graphics card family On-board graphics card family On-board graphics card model *	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 2280 (22 x 80 mm) X X Not available ✓ Intel X Intel Graphics	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95%
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board GPU manufacturer Discrete graphics card * On-board graphics card family On-board graphics card model * Audio	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 2280 (22 x 80 mm) X X Not available ✓ Intel X Intel Graphics Intel Graphics	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates	Kensington ✓ X ✓ 2.0 ✓ BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio Audio chip	SSD 1 TB 1 1 TB PCI Express 4.0 M.2 2280 (22 x 80 mm) X Not available Intel X Intel Graphics Intel Graphics Realtek ALC3306	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates Compliance certificates Certification	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m RoHS
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio Audio chip Audio system	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 2280 (22 x 80 mm) X X Not available ✓ Intel X Intel Graphics Intel Graphics	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates Compliance certificates Certification Sustainability	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m RoHS MIL-STD-810H military test passed
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio Audio chip	SSD 1 TB 1 1 TB PCI Express 4.0 M.2 2280 (22 x 80 mm) X Not available Intel X Intel Graphics Intel Graphics Intel Graphics Olby Atmos	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates Compliance certificates Certification	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m RoHS
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio Audio chip Audio system Number of built-in speakers	SSD 1 TB 1 1 TB PCI Express 4.0 M.2 2280 (22 x 80 mm) X X Not available Intel X Intel Graphics Intel Graphics Intel Graphics Obley Atmos 2	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates Compliance certificates Certification Sustainability Sustainability certificates	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m RoHS MIL-STD-810H military test passed ENERGY STAR, EPEAT Gold, ErP,
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio Audio chip Audio system Number of built-in speakers Speaker power	SSD 1 TB 1 1 TB PCI Express 4.0 M.2 2280 (22 x 80 mm) X X Not available Intel X Intel Graphics	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates Compliance certificates Certification Sustainability Sustainability certificates Weight & dimensions	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m RoHS MIL-STD-810H military test passed ENERGY STAR, EPEAT Gold, ErP, TCO
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio Audio chip Audio system Number of built-in speakers Speaker power Built-in microphone	SSD 1 TB 1 1 TB PCI Express 4.0 M.2 2280 (22 x 80 mm) X X Not available Intel X Intel Graphics Intel Graphics Intel Graphics Realtek ALC3306 Dolby Atmos 2 2 W ✓	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates Compliance certificates Certification Sustainability Sustainability certificates Weight & dimensions Width	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m ROHS MIL-STD-810H military test passed ENERGY STAR, EPEAT Gold, ErP, TCO 312.8 mm
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio Audio chip Audio system Number of built-in speakers Speaker power Built-in microphone	SSD 1 TB 1 1 TB PCI Express 4.0 M.2 2280 (22 x 80 mm) X X Not available Intel X Intel Graphics Intel Graphics Intel Graphics Realtek ALC3306 Dolby Atmos 2 2 W ✓	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Maximum shipping altitude Certificates Compliance certificates Certification Sustainability Sustainability certificates Weight & dimensions Width Depth	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m ROHS MIL-STD-810H military test passed ENERGY STAR, EPEAT Gold, ErP, TCO 312.8 mm 217.7 mm
Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio Audio chip Audio system Number of built-in speakers Speaker power Built-in microphone	SSD 1 TB 1 1 TB PCI Express 4.0 M.2 2280 (22 x 80 mm) X X Not available Intel X Intel Graphics Intel Graphics Intel Graphics Realtek ALC3306 Dolby Atmos 2 2 W ✓	Cable lock slot Cable lock slot type Fingerprint reader Smart card reader Windows Hello Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates Compliance certificates Certification Sustainability Sustainability certificates Weight & dimensions Width	Kensington X X 2.0 BIOS, Power on, SSD, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m ROHS MIL-STD-810H military test passed ENERGY STAR, EPEAT Gold, ErP, TCO 312.8 mm

Packaging content	
AC adapter included *	✓
Stylus pen	✓





198153464753

0198153464753

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.