

NETGEAR GS516UP Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey



Brand : NETGEAR

Product code: GS516UP-100NAS

Product name : GS516UP

- PLUG AND PLAY: Simple setup with no software or configuration needed
- POWER-OVER-ETHERNET: large 380W total PoE budget with 8 Ultra60 PoE++ ports and 8 PoE+ ports to power wireless AP, 4K/8K IP Cameras, LED lights, IoT devices, and much more
- COMPACT, FLEXIBLE FORM FACTOR - Small case with internal power supply and whisper-quiet fans, perfect for desktop, wall-mount, or rackmount deployment
- EASY-MONITORING - Per port LEDs for port activity and speed
- GIGABIT ETHERNET - 16 auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with up to 32Gb non-blocking switching
- PoE AUTO-BALANCE - unique PoE technology automatically balances the PoE power based on the device needs independent of PoE class detected

Gigabit Unmanaged Switch Series (GS516UP) 16-Port Gigabit Ethernet High-Power PoE+ Unmanaged Switch with 8-Ports PoE++ (380W)

Management features		Performance	
Switch type *	Unmanaged	Mean time between failures (MTBF)	1213791 h
Quality of Service (QoS) support	✓	Power	
Ports & interfaces		Power source *	PoE
Basic switching RJ-45 Ethernet ports quantity *	16	AC input voltage	100 - 240 V
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	AC input frequency	50/60 Hz
		Input current	8 - 4 A
		Power consumption (max)	456.8 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.3ae, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3p, IEEE 802.3u	Power over Ethernet (PoE) *	✓
10G support *	✗	Power over Ethernet plus (PoE+) ports quantity	16
Full duplex	✓	Power over Ethernet (PoE) power per port	60 W
Half duplex	✓	Total Power over Ethernet (PoE) budget	380 W
Auto MDI/MDI-X	✓	Operational conditions	
Data transmission		Operating temperature (T-T)	0 - 50 °C
Switching capacity *	32 Gbit/s	Storage temperature (T-T)	-20 - 70 °C
MAC address table *	8000 entries	Operating relative humidity (H-H)	10 - 90%
Jumbo frames support	✓	Operating altitude	0 - 3000 m
Packet forwarding rate (1 Gbps)	1448000 pps	Heat dissipation	1559.5152 BTU/h
Design		Weight & dimensions	
Rack mounting *	✓	Width	390 mm
Product colour	Grey	Depth	220 mm
Housing material	Metal	Height	43 mm
LED indicators	Activity, Link, PoE, Power, Speed	Weight	2.6 kg
Number of fans	3 fan(s)		



606449149739

0606449149739

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.