Verbatim USB-C Essentials Multiport Hub 4 ports: HDMI, USB-C PD, USB-A 3.2 Gen 1, USB-A

Brand: Verbatim Product code: 32155

Product name: USB-C Essentials Multiport Hub 4 ports:

HDMI, USB-C PD, USB-A 3.2 Gen 1, USB-A

USB-C Essentials Multiport Hub 4 ports: HDMI, USB-C PD, USB-A 3.2 Gen 1, USB-A

Verbatim USB-C Essentials Multiport Hub 4 ports: HDMI, USB-C PD, USB-A 3.2 Gen 1, USB-A:

Simplify Connections

Easily expand your connectivity with four essential ports, including HDMI, USB-C® PD 3.0, USB-A 3.2 Gen 1, and USB-A 2.0. This hub is designed to connect your laptop to external displays, USB drives, and other peripherals, making it a versatile addition to your workspace.

High-Speed Data Transfer

With USB 3.2 Gen 1, enjoy data transfer speeds up to 5Gb/s. This enables quick sharing of files and efficient syncing of devices. The additional USB-A 2.0 port offers compatibility with older devices at speeds up to 480Mbps.

Impressive Display Output

Connect to an external display with the HDMI port, which supports 4K resolution at 30Hz. This allows for an enhanced viewing experience, perfect for presentations, video conferencing, or streaming content.

Ports & interfaces		
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	
Hub interfaces *	HDMI, USB 2.0 Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-A	
USB 2.0 ports quantity	1	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	
HDMI ports quantity	1	
Ports quantity *	4	
Features		
Data transfer rate *	5000 Mbit/s	
Supported graphics resolutions	3840 x 2160	
Maximum resolution (HDMI)	3840 x 2160 pixels	
Product colour	Grey	
Housing material	Acrylonitrile butadiene styrene (ABS), Aluminium	
USB Power Delivery (USB PD)	✓	
USB Power Delivery revision	3.0	
USB Power Delivery up to	100 W	
HD type	4K Ultra HD	
Number of displays supported	1	
Cable type	Round cable	
Cable length	0.15 m	
Plug and Play	✓	
Country of origin	China	
Power		
Power supply type	USB	
Input voltage	5 - 20 V	
Output voltage	5 V	
Output current	0.9 A	



Weight & dimensions	
Width Depth Height Weight	29.7 mm 96.7 mm 11 mm 51 g
Packaging data	
Quantity per pack Package width Package depth Package height Package weight Package type	1 pc(s) 85 mm 155 mm 20 mm 100 g Box
Packaging content	
Quick start guide	✓
Operational conditions	
Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 °C 40 °C 0 - 40 °C -20 - 85 °C 20 - 90%
Logistics data	
Pallet gross width Pallet gross length	100 cm 120 cm
Pallet gross height Pallet gross weight Master (outer) case width Master (outer) case length Master (outer) case height Master (outer) case gross weight	120 cm 255 kg 256 mm 345 mm 236 mm 5.3 kg
	Width Depth Height Weight Packaging data Quantity per pack Package width Package depth Package height Package weight Package type Packaging content Quick start guide Operational conditions Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Logistics data Pallet gross width Pallet gross height Pallet gross weight Master (outer) case width Master (outer) case height

System requirements		Technical details	
Windows operating systems supported Mac operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma	Pallet net height Pallet net length Pallet net width Pallet net weight Compliance certificates	12 cm 120 cm 100 cm 12 kg CE, Electromagnetic Compatibility (EMC), Federal Communications Commission (FCC), Low Voltage Directive (LVD), REACH, RoHS, UKCA
Linux operating systems supported Other operating systems supported			





023942321552

0023942321552

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.