

CyberPower PR1000LCDRT1U uninterruptible power supply (UPS)
Line-Interactive 1 kVA 800 W 7 AC outlet(s)

Brand : CyberPower

Product code: PR1000LCDRT1U

Product name : PR1000LCDRT1U



Line Interactive, PFC, NEMA 5-15P, 1000 VA, 800 W, 1030 J, NEMA 5-15R x 7, 1U
CyberPower PR1000LCDRT1U. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 800 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 7 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 3.5 min, Typical backup time at half load: 13 min. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 1U. Compliance certificates: RoHS



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount/Tower
Output power capacity *	1 kVA	Rack capacity	1U
Output power *	800 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (max) *	120 V	LED indicators	✓
Input frequency *	47/63 Hz	Operational conditions	
Output operation voltage (max)	120 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	60 Hz	Storage temperature (T-T)	-15 - 45 °C
Surge energy rating	1030 J	Storage relative humidity (H-H)	0 - 90%
Power factor	0.8	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 15000 m
EMI/RFI noise filtering	✓	Certificates	
Ports & interfaces		Compliance certificates	RoHS
AC outlet types	NEMA 5-15R	Safety regulation & standards	
Power plug	NEMA 5-15P	Safety	UL1778 4th, cUL CSA C22.2 No 107.3-05, FCC/DOC Class A
AC outlets quantity	7 AC outlet(s)	Sustainability	
Serial ports quantity	1	Sustainability certificates	ENERGY STAR
Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Width	438.1 mm
Number of batteries supported	4	Depth	401.3 mm
Typical backup time at full load	3.5 min	Height	44.5 mm
Typical backup time at half load	13 min	Weight	16.3 kg
Battery recharge time	6 h	Packaging data	
Hot-swap battery	✓	Package width	528.3 mm
		Package depth	492.8 mm

Packaging data	
Package height	157.5 mm
Package weight	19.3 kg
Other features	
Overload protection	✓
Output voltage	120 V



0649532610242



649532610242

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.