TP-Link Archer AX3000 Dual-Band Wi-Fi 6 Air Router

Brand : TP-Link

Product family: Archer

Product code: ARCHER AIR R5

Product name : AX3000 Dual-Band Wi-Fi 6 Air Router

- Next-Gen Gigabit Wi-Fi 6 Speed—2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz band ensure smoother streaming and faster downloads

- Smart Antennas – Uses intelligent algorithms to auto-detect your devices' locations and adjust antennas' direction for all-round stable signals

- Ultra-Low Latency—Enables more responsive gaming and video chatting

- TP-Link HomeShield - Enhanced security defends against the latest cyber threats

- EasyMesh-Compatible - Works with EasyMesh-compatible routers to create a whole home seamless mesh network

- Flexible Installation – Easy to stick or mount on the wall with 3M adhesives and the attached plastic bracket

AX3000, Wi-Fi 6, 2.4/5 GHz, 574 + 2402 Mbps, 1x Gigabit WAN, 1x Gigabit, 210 x 148 x 10.8 mm





WAN connection		Management features	
Ethernet WAN *	✓	WPS push button	1
DSL WAN *	×	Security	
SIM card slot * 3G/4G USB modem compatibility * WAN connection type	× × RI-45	Security algorithms Guest access	WPA, WPA-PSK, WPA2, WPA2-PSK, WPA3
Wireless LAN features	19-45	Protocols	
Wi-Fi band * Top Wi-Fi standard * WLAN data transfer rate (max) * Wi-Fi standards WLAN data transfer rate (first band) WLAN data transfer rate (second band) Network	Dual-band (2.4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) 2976 Mbit/s 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax) 574 Mbit/s 2402 Mbit/s	DHCP server Supported network protocols Design Product colour Wall mountable Product type * Certificates Certification	✓ IPv4, IPv6 White ✓ Tabletop router FCC, CE, RoHS
Ethernet LAN * Ethernet LAN interface type * Ethernet LAN data rates Number of guest networks (2.4 GHz) Number of guest networks (5 GHz)	 ✓ Gigabit Ethernet 10,100,1000 Mbit/s 1 1 	Packaging content Manual Antenna Antenna design * Power Power source type *	✓ Internal USB

Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports *	1	Operating temperature (T-T)	0 - 40 °C
USB port *	1	Storage temperature (T-T)	-40 - 60 °C
USB charging port	1	Operating relative humidity (H-H)	10 - 90%
Management features		Storage relative humidity (H-H)	5 - 90%
Quality of Service (QoS) support		Weight & dimensions	
Reset button		Width	148 mm
		Depth	10.8 mm
		Height	210 mm

Package type

Box





4895252500653

4895252500660

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.