



APC Smart-UPS uninterruptible power supply (UPS) 1.92 kVA 1920 W 10 AC outlet(s)

Brand : APC

Product code: SMT2200US

Product name : Smart-UPS

1920W, 1920VA, 120V, SmartSlot, 8 x NEMA 5-15R & 2 x NEMA 5-20R Out, NEMA 5-20P In, LCD  
APC Smart-UPS. Output power capacity: 1.92 kVA, Output power: 1920 W, Waveform: Sine. AC outlet types: NEMA 5-15R, NEMA 5-20R, Power plug: NEMA 5-20P, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 7.5 min, Typical backup time at half load: 22.5 min. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS



Features		Design	
Output power capacity *	1.92 kVA	Form factor *	Tower
Output power *	1920 W	Cable length	1.83 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	75 V	Display type	LCD
Input operation voltage (max) *	154 V	Operational conditions	
Input frequency *	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	530 J	Storage temperature (T-T)	-15 - 45 °C
Efficiency	98%	Operating relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Storage relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	5%	Operating altitude	0 - 3000 m
Noise level	45 dB	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	Certificates	
Audible alarm modes	Battery replacement	Compliance certificates	RoHS
Ports & interfaces		Sustainability	
AC outlet types	NEMA 5-15R, NEMA 5-20R	Sustainability certificates	ENERGY STAR
Power plug	NEMA 5-20P	Weight & dimensions	
AC outlets quantity	10 AC outlet(s)	Width	196 mm
USB 2.0 ports quantity	1	Depth	544 mm
Battery		Height	432 mm
Battery technology	Sealed Lead Acid (VRLA)	Weight	50.9 kg
Typical backup time at full load	7.5 min	Packaging data	
Typical backup time at half load	22.5 min	Package weight	60.9 kg
Battery recharge time	3 h	Other features	
Replacement battery cartridge	RBC55	Nominal output voltage	120 V
		Nominal input voltage	120 V
		Output connection type	8 x NEMA 5-15R & 2 x NEMA 5-20R

#### Other features

Package dimensions (WxDxH)	381 x 762 x 559 mm
----------------------------	--------------------



0731304305620



731304305620

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.