APC

APC SCL500RM1UC uninterruptible power supply (UPS) Line-Interactive 0.5 kVA 400 W 4 AC outlet(s)

Brand : APC

Product code: SCL500RM1UC

Product name : SCL500RM1UC

Smart-UPS Li-Ion, Short Depth 500VA, 120V with SmartConnect

APC SCL500RM1UC uninterruptible power supply (UPS) Line-Interactive 0.5 kVA 400 W 4 AC outlet(s):

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
APC SCL500RM1UC. UPS topology: Line-Interactive, Output power capacity: 0.5 kVA, Output power: 400 W. AC outlet types: NEMA 5–15R, Power plug: NEMA 5-15P, AC outlets quantity: 4 AC outlet(s). Battery technology: Lithium-Ion (Li-Ion), Battery life (max): 10 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Silver, Rack capacity: 1U. Compliance certificates: RoHS, Certification: CSA C22.2 NO. 107.3, cULus, FCC 15 Class A, NOM, UL 1778, UL 1973

Features

UPS topology *	Line-Interactive
Output power capacity *	0.5 kVA
Output power *	400 W
Waveform *	Sine
Input operation voltage (min) *	92 V
Input operation voltage (max) *	139 V
Input frequency *	47/63 Hz
Output operation voltage (min)	120 V
Output operation voltage (max)	120 V
Output frequency	50/60 Hz
Output voltage regulation	5%
Automatic Voltage Regulation (AVR)	✔
Surge energy rating	680 J
Response time	6 ms
Noise level	45 dB
Audible alarm(s)	✔
Audible alarm modes	Alarm when on battery

Ports & interfaces

AC outlet types	NEMA 5–15R
Power plug	NEMA 5-15P
AC outlets quantity	4 AC outlet(s)
USB port	✔
USB 2.0 ports quantity	1
USB port type	USB Type-A
Ethernet LAN (RJ-45) ports	1

Battery

Battery technology	Lithium-Ion (Li-Ion)
Battery life (max)	10 year(s)

Battery

Battery recharge time	3 h

Design

Form factor *	Rackmount
Rack capacity	1U
Product colour *	Black, Silver
LED indicators	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 1968 m
Non-operating altitude	0 - 14763 m

Certificates

Compliance certificates	RoHS
Certification	CSA C22.2 NO. 107.3, cULus, FCC 15 Class A, NOM, UL 1778, UL 1973

Packaging content

Rack mount kit	✔
Cables included	USB cable
Quick installation guide	✔

Weight & dimensions

Width	432 mm
Depth	232 mm
Height	44 mm
Weight	4.18 kg

Packaging data

Package width	590 mm
Package depth	337 mm
Package height	168 mm
Package weight	6 kg

0731304344551

731304344551

Catalog Object Cloud