

TP-Link Omada AX3000 Indoor/Outdoor WiFi 6 Access Point

Brand : TP-Link

Product family: Omada

Product code: EAP650 D30-OUTDOOR

Product name : AX3000
Indoor/Outdoor WiFi 6 Access Point




- Superior WiFi 6 Speeds: 2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz
- Directional Ultra-Range Coverage: Equipped with built-in high-gain directional antennas to deliver precise and extended coverage
- Ideal for Warehouses and Outdoor Scenes: Features an IP68 waterproof enclosure with -30°C to +70°C operating range
- 802.11k/v/r Seamless Roaming: Ensures uninterrupted connectivity for AGVs and handheld scanners
- Flexible Deployment: Supports 802.3at PoE and Omada Mesh technology
- Centralized Cloud Management: Control everything from a single interface anywhere via the Omada app or Web UI

574 Mbps (2.4 GHz) + 2402 Mbps (5 GHz), 802.3at PoE, 1x Gigabit Ethernet, IP68, 207.5 x 58 x 230 mm
TP-Link Omada AX3000 Indoor/Outdoor WiFi 6 Access Point. 2.4 GHz, 5 GHz, Maximum data transfer rate: 3000 Mbit/s. Security algorithms: SNMP, SNMPv2, SNMPv3. Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White




Features		Ports & interfaces	
2.4 GHz *	✓	Ethernet LAN (RJ-45) ports *	1
5 GHz *	✓	Power	
6 GHz *	✗	Power over Ethernet (PoE) *	✓
Maximum data transfer rate *	3000 Mbit/s	Power over Ethernet (PoE) type supported	Passive PoE
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	AC input voltage	48 V
Maximum data transfer rate (5 GHz)	2402 Mbit/s	Design	
Ethernet LAN data rates	10,100,1000 Mbit/s	Placement *	Ceiling, Wall
	IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11k, IEEE 802.11n, IEEE 802.11r, IEEE 802.11v, IEEE 802.3at	Product colour *	White
Networking standards		Antenna	
Bluetooth	✓	Antenna type *	Internal
Automatic channel selection	✓	Weight & dimensions	
MIMO	✓	Width	207.5 mm
MIMO type	Multi User MIMO	Depth	58 mm
Band steering	✓	Height	230 mm
Airtime Fairness (ATF)	✓	Packaging content	
Security		Quantity per pack	1 pc(s)
Security algorithms *	SNMP, SNMPv2, SNMPv3	Mounting kit	✓
MAC address filtering	✓	Quick start guide	✓
Remote Authentication Dial-In User Service (RADIUS)	✓	Other features	
Management features		Horizontal beam width	30°
Web-based management	✓	Vertical beam width	30°



8885020625042



1210002612739



810142822763

0810142822763

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.