

## TP-Link VIGI InSight S445ZI Turret IP security camera Outdoor 2688 x 1520 pixels Ceiling

Brand: TP-Link Product family: VIGI Product code: INSIGHT S445ZI

Product name: InSight S445ZI

- 5X Optical Zoom for Easy Installation and Monitoring
- 4MP Super-High Definition and IR Range Up to 60m (197ft)
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Audio and Alarm Interface Available
- IP67 Weatherproof and IK10 Vandal Proof
- H.265+ Compression Technology

InSight S445ZI VIGI 4MP IR Motorized Varifocal Turret Network Camera

TP-Link VIGI InSight S445ZI. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling, Product colour: White, Form factor: Turret. Angle of rotation: 360°, Lens viewing angle, horizontal: 29.6–102, Lens viewing angle, vertical: 16.8–53.8. Sensor type: CMOS, Optical sensor size: 25.4 / 2.9 mm (1 / 2.9"). Optical zoom: 5x, Focal length range: 2.7 - 13.5 mm, Focus: Motorized





Performance		Video	
Type *	IP security camera	Region of Interest (ROI) encoding	✓
Placement supported *	Outdoor	Smart IR	✓
Connectivity technology *	Wired	Audio	
Wide Dynamic Range (WDR)	✓	Audio system	2-way
Day/night mode	•	Audio input channels	1.0 channels
Infrared (IR) cut-off filter	✓	Audio output channels	1.0 channels
Remote viewing	<b>✓</b>	Audio formats supported	G.711 A-law
Dynamic range	120 dB	Sample rate	8 kHz
Design		Signal-to-Noise Ratio (SNR)	52 dB
Form factor *	Turret	Built-in microphone	✓
Mounting type *	Ceiling	Number of microphones	1
Product colour *	White	Bit rate range	0 - 64 Kbit/s
Protection features Water	Metal	Network	
	Waterproof	Ethernet LAN *	<b>✓</b>
International Protection (IP) code	IP67	Networking standards	IEEE 802.3af, IEEE 802.3at
Weatherproof  amera	0 lx	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6,
Minimum illumination	0 IX 360°		ARP
<b>3</b> · · · · · ·	29.6-102	Wi-Fi *	×
Lens viewing angle, vertical	16.8-53.8	Bluetooth *	×
Lens viewing angle, diagonal	34.1-122.8	Live view	✓
Tilt angle range	0 - 77°	Number of simultaneous live view channels	6 channels
Pan range Camera shutter speed	0 - 360° 1/3 to 1/10000	Storage	
Number of Privacy masking areas	4	Card reader integrated	<b>✓</b>
		Compatible memory cards	MicroSD (TransFlash)

Image sensor		Storage	
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")	Maximum memory card size	512 GB
Progressive scan	✓	Ports & interfaces	
Sensor type *	CMOS	Ethernet LAN (RJ-45) ports	1
Lens system		DC-in jack	✓
Zoom capability	✓	Security	
Optical zoom	5x	Alarm input channels	1
Number of lenses *	1	Alarm output channels	1
Focal length range	2.7 - 13.5 mm	Built-in siren	✓
Auto focus	<b>✓</b>	Password protection	✓
Focus	Motorized	Video motion detection	<b>✓</b>
Maximum aperture number	1.6 66 m	IP address filtering	<b>✓</b>
Detect distance (wide) Detect distance (tele)	207 m	HTTPS encryption	<b>✓</b>
Observe distance (wide)	28 m	Alert notification type	Push notification
Observe distance (tele)	86 m	Privacy protection	<b>✓</b>
Recognize distance (wide)	13 m	Motion sensor	<b>✓</b>
Recognize distance (tele)	41 m	Mirror	<b>✓</b>
Identify distance (wide)	7 m	Human and vehicle targets	
Identify distance (tele)	21 m	classification	•
Night vision		Digest authentication	✓
Night vision *	✓	Management features	
Night vision distance	60 m	Web browser	<b>✓</b>
LED type	IR	Cloud-managed *	<b>✓</b>
Number of illumination LEDs	4	Reset button	<b>✓</b>
Infra-red wavelength	850 nm	Power	
Video		Power source type *	DC, PoE
Maximum resolution *	2688 x 1520 pixels	Power consumption (max)	10.8 W
Total megapixels * Video compression formats	4 MP H.264, H.264+, H.265, H.265+	Power consumption (Power over	12 W
video compression formats	1920 x 1080 (HD 1080), 2048 x	Ethernet (PoE))	
Supported graphics resolutions	1280, 2304 x 1296, 2560 x 1440,	DC output voltage	12
N	2688 x 1520	Operational conditions	
Video recording	<b>✓</b>	Operating temperature (T-T)	-30 - 60 °C
Video streaming	✓	Storage temperature (T-T)	-40 - 60 °C
Noise reduction	20 1 1 1	Operating relative humidity (H-H)	0 - 95%
Noise reduction technology	3D noise reduction	Storage relative humidity (H-H)	0 - 95%
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Weight & dimensions	
Bit rate control	Constant Bit Rate (CBR)/Variable Bit	Height	92.5 mm
	Rate (VBR)	Diameter Weight	11.2 cm 710 g
Bit rate	Main Stream: 256 Kbps to 6 Mbps, Sub-Stream: 512 Kbps to 1024 Kbps	-	7 10 g
Back Light Compensation (BLC)	<b>✓</b>	Packaging data	000 =
Highlight Compensation (HLC)	✓	Package weight Package type	960 g Box
Digital Wide Dynamic Range	<b>✓</b>		DOX
(DWDR)		Packaging content	1
		Number of cameras *	1
		Mounting kit	v .
		Screws included	<b>v</b>
		Drilling template included	<b>v</b>
		Manual	v





1210002606318

8885020623550

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.