EPSON

Epson B11B205321 scanner Flatbed & ADF scanner 1200 x 1200 DPI A4 White

Brand : Epson

Product code: B11B205321

Product name : B11B205321

Flatbed & ADF, 1200 x 1200 dpi, A4/A5/B5, USB 2.0, 9.8 kg
Epson B11B205321. Maximum scan size: 216 x 1016 mm, Optical scanning resolution: 1200 x 1200 DPI,
Input colour depth: 48 bit. Scanner type: Flatbed & ADF scanner, Product colour: White. Sensor type:
CCD, Daily duty cycle (max): 4000 pages, Light source: ReadyScan LED. Auto document feeder (ADF)
input capacity: 100 sheets. Maximum ISO A-series paper size: A4, ISO A-series sizes (A0...A9): A4, A5,
ISO B-series sizes (B0...B9): B5

Scanning

Maximum scan size *	216 x 1016 mm
Optical scanning resolution *	1200 x 1200 DPI
Colour scanning	✔
Duplex scanning *	✔
Input colour depth	48 bit
Output colour depth	24 bit
Greyscale levels	16
ADF scan speed (b/w, A4)	40 ppm
ADF scan speed (colour, A4)	40 ppm
Duplex ADF scan speed (b/w, A4)	80 ipm
Duplex ADF scan speed (colour, A4)	80 ipm

Design

Scanner type *	Flatbed & ADF scanner
Product colour *	White

Performance

Sensor type *	CCD
Light source	ReadyScan LED
Scan file formats	JPG, PDF, TIFF
Daily duty cycle (max) *	4000 pages

Input capacity

Auto document feeder (ADF) input capacity	100 sheets

Paper handling

Maximum ISO A-series paper size *	A4
ISO A-series sizes (A0...A9)	A4, A5
ISO B-series sizes (B0...B9)	B5
Letter	✔
Legal	✔
Auto Document Feeder (ADF) media weight	50 - 128 g/m²

Paper handling

Maximum scan area (ADF)	216 x 1016 mm
Minimum scan area (ADF)	100 x 148 mm

Ports & interfaces

USB port *	✔
USB version	2.0
Optional connectivity	Ethernet
Standard interfaces	USB 2.0

Network

Ethernet LAN	✔

Power

Power supply type *	AC
Power consumption (typical)	45 W
Power consumption (standby)	1.6 W
AC input frequency	50 - 60 Hz
Input voltage	100-240 V

Weight & dimensions

Width	495 mm
Depth	360 mm
Height	217 mm
Weight	9.8 kg

Sustainability

Sustainability certificates	ENERGY STAR

System requirements

Windows operating systems supported	Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64, Yes
Mac operating systems supported	Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion

Operational conditions

Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-25 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	10 - 85%

Catalog Object Cloud