QNAP

QNAP TS-216G-US NAS/storage server Tower Cortex-A Cortex-A55 4 GB White

Brand : QNAP

Product name : TS-216G-US

Product code: TS-216G-US

QNAP TS-216G-US. Type: NAS. Chassis type: Tower. Device class: Large Enterprise Business. Processor family: Cortex-A, Processor model: Cortex-A55, Processor frequency: 2 GHz. Internal memory: 4 GB

Storage

Storage drive interface *	Serial ATA
Supported storage drive interfaces	Serial ATA
Storage drive size	2.5/3.5"
Storage drive sizes supported	2.5,3.5"
Hot-swap drive bays	✔
Storage drives installed *	✘
Number of storage drives supported *	2
Installed storage drive type *	✘
Supported storage drive types *	HDD & SSD

Processor

Processor manufacturer *	ARM
Processor family *	Cortex-A
Processor model *	Cortex-A55
Processor frequency *	2 GHz
Processor cores	4
Processor architecture	ARM Cortex-A55
CPU configuration (max)	1
On-board graphics card model	Arm Mali-G52

Memory

Internal memory *	4 GB
Maximum RAM supported	4 GB
ECC	✘
Flash memory	4000 MB

Ports & interfaces

Concurrent connections	200

Design

Chassis type *	Tower
Cooling type *	Active
Product colour	White
Number of fans	1 fan(s)
Fan diameter	7 cm
LED indicators	HDD, LAN, Status, USB
Built-in display	✔
Cable lock slot	✔
Cable lock slot type	Kensington

Performance

Type *	NAS
Device class *	Large Enterprise Business
Buzzer	✔
Reset button	✔
On/off switch	✔
USB copy function	✔

Power

Power supply location	Built-in
Power supply unit (PSU) capacity	65 W
Number of power supply units	1
Power consumption (typical)	13.907 W
Power consumption (sleep)	4.973 W

Network

Ethernet LAN *	✔
Ethernet LAN data rates	10,100,1000,2500 Mbit/s
Jumbo frames support	✔
Wake-on-LAN ready	✔
WLAN adapter supported	✔

Ports & interfaces

USB port *	✔
USB 2.0 ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Ethernet LAN (RJ-45) ports *	2

Power

AC input voltage	100 - 240 V

Weight & dimensions

Width *	102 mm
Depth *	220.6 mm
Height *	165 mm
Weight	1.45 kg
Package weight	2.41 kg

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	-20 - 70 °C

Other features

Warranty period	2 year(s)

Catalog Object Cloud