StarTechcom

StarTech.com 8m (26.2ft) LC to LC (UPC) OS2 Single Mode Duplex Fiber Optic Cable, 9/125 μm , 100G, Bend Insensitive, Low Insertion Loss - LSZH Fiber Jumper Cord

Brand : StarTech.com

Product code: SMDOS2LCLC8M

 $\begin{array}{l} \mbox{Product name : $8m (26.2ft) LC to LC (UPC) OS2 Single Mode} \\ \mbox{Duplex Fiber Optic Cable, $9/125 \mu m, 100G, Bend Insensitive,} \\ \mbox{Low Insertion Loss - LSZH Fiber Jumper Cord} \end{array}$

StarTech.com 8m (26.2ft) LC to LC (UPC) OS2 Single Mode Duplex Fiber Optic Cable, 9/125, 100G, LSZH Fiber Jumper Cord


StarTech.com 8m (26.2ft) LC to LC (UPC) OS2 Single Mode Duplex Fiber Optic Cable, 9/125µm, 100G, Bend Insensitive, Low Insertion Loss - LSZH Fiber Jumper Cord. Cable length: 8 m, Cable type: LC/UPC, Fibre optic type: OS2, Connector 1: LC, Connector 2: LC, Core diameter: 9 µm, Full duplex

| Features | | Certificates | |
|--|--|--|----------------------------|
| Cable length * | 8 m | Compliance certificates | CE |
| Fibre optic type Connector 1 * | nector 1 * LC nector 2 * LC nector 1 gender * Male nector 2 gender * Male | Operational conditions | |
| Connector 2 * Connector 1 gender * Connector 2 gender * Connector polish type | | Operating temperature (T-T) Storage temperature (T-T) | -20 - 60 °C -20 - 60 °C |
| Cable type * | LC/UPC | Weight & dimensions | |
| Product colour * Full duplex | ur* Yellow ✓ | Cable diameter Bending radius | 2 mm 1 cm |
| Core diameter Cladding diameter | 9 μm 125 μm | Packaging data | |
| Fiber mode structure Wavelengths supported | de structure Single-mode lights supported 1260,1280,1300,1310,1383,1490,1550,1590,1600,1625 nm nm nsfer rate 10 Gbit/s noss 0.3 dB | Package width Package depth | 200 mm 220 mm |
| Data transfer rate Insertion loss Return loss | | Package height Package weight | 8 mm 62.4 g |
| Jacket material * | Low smoke zero halogen (LSZH), Polypropylene | Packaging content | |
| Sustainability | | Quantity per pack | 1 pc(s) |
| Sustainability compliance | 1 | Other features | |
| | | Attenuation (max) | 0.35 dB/km |
| | | Logistics data | |
| | | Master (outer) case width | 380 mm |











065030901758

0065030901758

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.