

APC SMTL1000RM2UC uninterruptible power supply (UPS) Line-Interactive 1 kVA 800 W 6 AC outlet(s)



Brand : APC Product code: SMTL1000RM2UC

Product name: SMTL1000RM2UC

Smart-UPS Li-Ion, Short Depth 1000VA, 120V with SmartConnect

APC SMTL1000RM2UC uninterruptible power supply (UPS) Line-Interactive 1 kVA 800 W 6 AC outlet(s):

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

APC SMTL1000RM2UC. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 800 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 6 AC outlet(s). Battery technology: Lithium-Ion (Li-Ion), Battery life (max): 10 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CSA C22.2 NO. 107.3, FCC Part 15 Class A, NOM, UL 1778, UL 1973



DUS topology * Line-Interactive Battery technology Lithium-Ion (Li-Ion) Output power capacity * 1 kVA Battery life (max) 10 year(s) Output power * 800 W Battery recharge time 3 h Waveform * Sine Mayer form * Sine Input operation voltage (min) * 75 V Input operation voltage (max) * 154 V Input operation voltage (max) * 154 V Input operation voltage (min) * 120 V Output operation voltage (max) * 120 V Output voltage regulation 5% Operating temperature (T-T) Output voltage regulation 5% Operating temperature (T-T) 40 °C Audible alarm (s)				
Output power capacity** 1 kVA Battery life (max) 10 year(s) Output power** 800 W Battery recharge time 3 h Waveform** Sine Design Input operation voltage (min)* 75 V Form factor* Rackmount Input operation voltage (max)* 154 V Rack capacity 2U Output operation voltage (min) 120 V Product colour* Black Output peration voltage (max) 120 V Product colour* Black Output frequency* 50/60 Hz LCD LCD Output frequency 50/60 Hz LED indicators ✓ Output frequency 50/60 Hz LED indicators ✓ Surge energy rating 680 J Operating altitude 0 - 40 °C Surge energy rating 680 J Operating temperature (T-T) -40 °C Noise level 41 dB Storage temperature (T-T) -40 °C Aduible alarm modes Alarm when on battery, Low battery alarm Non-operating altitude 0 - 7500 m Ports & Interfaces NEMA 5-15R Certificates <td>Features</td> <td></td> <td>Battery</td> <td></td>	Features		Battery	
Input operation voltage (min) 75 V FOR Porm factor * Rackmount Input operation voltage (max) 154 V Rack capacity 2U Solfoe Hz Solfoe Hz Cable length 2.44 m Black 2.44 m Solfoe Hz Cable length 2.44 m Solfoe Hz Solfoe Hz Cable length 2.44 m Solfoe	UPS topology * Output power capacity * Output power *	1 kVA 800 W Sine 75 V 154 V 50/60 Hz 120 V 120 V 50/60 Hz 5% 680 J 6 ms 41 dB	Battery life (max)	10 year(s)
Reduible alaim modes alarm Certificates Compliance certificates RoHS AC outlet types NEMA 5-15R Power plug NEMA 5-15P AC outlets quantity 6 AC outlet(s) Weight & dimensions Width 438 mm USB port type USB Type-A Depth Serial interface Ferial interface type Ethernet LAN (RJ-45) ports SmartSlot Package width Package width Package weight	Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) Output frequency Output voltage regulation Surge energy rating Response time Noise level Audible alarm(s)		Design Form factor * Rack capacity Cable length Product colour * Display type LED indicators Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating altitude	2U 2.44 m Black LCD
AC outlet types Power plug NEMA 5-15P Region (SA C22.2 NO. 107.3, FCC Part 15 Class A, NOM, UL 1778, UL 1973) AC outlets quantity AC outlets quantity AC outlets quantity Begin to type USB Type-A USB Type-A Serial interface Serial interface Final interface type	Audible alarm modes			0 - 7500 m
USB port type USB Type-A USB Type-A Depth Serial interface ✓ Height Weight Weight 16.3 kg Packaging data Package width Package depth Package depth Package weight	Ports & interfaces AC outlet types Power plug		·	CSA C22.2 NO. 107.3, FCC Part 15
USB port type USB Type-A Depth 318 mm Height 86 mm Serial interface type RJ-45 Weight 16.3 kg Packaging data Package width Package width Package depth Package depth Package height Package weight 18.6 kg Logistics data	AC outlets quantity	6 AC outlet(s)	Weight & dimensions	
Packaging data Package width Package depth Package height Package weight	USB port USB port type Serial interface Serial interface type Ethernet LAN (RJ-45) ports SmartSlot	USB Type-A ✓ RJ-45 1	Depth Height	318 mm 86 mm
Package width 584 mm Package depth 472 mm Package height 229 mm Package weight 18.6 kg Logistics data			Packaging data	
•			Package depth Package height Package weight	472 mm 229 mm
				16 pc/s)





731304341987

0731304341987

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.