## **PHILIPS**

## Philips 50BDL3511Q/00 Signage Display Digital A-board 127 cm (50") 500 cd/m<sup>2</sup> 4K Ultra HD Black 18/7



Product name: 50BDL3511Q/00

- Easy-setup 18/7 display
- 50
- Direct LED Backlight
- Ultra HD

 $50^{\shortparallel}~4\text{KUHD}~3840~x~2160~VA,~400~cd/m^2,~4000:1,~16:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~16:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~16:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~16:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~16:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~HDMI,~I6:9,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~Response~8\text{ms},~1.07~Billion,~DVI-I,~USB,~DVI-$ 


RJ-45, RS232C, IR, 18/7

Philips 50BDL3511Q/00. Product design: Digital A-board. Display diagonal: 127 cm (50"), Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m², HD type: 4K Ultra HD. Operating hours

(hours/days): 18/7. Product colour: Black

Display		Design	
Panel type LED backlighting type Display diagonal * Display resolution * Display brightness * HD type * Touchscreen * Native aspect ratio Response time Contrast ratio (typical)	VA Direct-LED 127 cm (50") 3840 x 2160 pixels 500 cd/m² 4K Ultra HD  x 16:9 8 ms 4000:1	Pesign  VESA mounting *  Panel mounting interface Bezel width (bottom) Bezel width (side) Bezel width (top)  Performance  Purpose *  On Screen Display (OSD)	✓ 400 x 400 mm 1.49 cm 1.49 cm 1.49 cm  Commercial ✓ Arabic, Simplified Chinese,
Contrast ratio (dynamic) Viewing angle, horizontal Viewing angle, vertical	500000:1 178° 178°	On Screen Display (OSD) languages  Operating hours (hours/days)	Traditional Chinese, English, French, Italian, Japanese, Polish, Russian, Turkish 18/7
Display number of colours	1.07 billion colours	Power	,
Pixel pitch Display diagonal (metric) Haze rate	0.2854 x 0.2854 mm 125.7 cm 2%	Power  Power consumption (typical) *  Power consumption (standby) *  Energy efficiency class (SDR)	130 W 0.5 W G
Ports & interfaces		Energy consumption (SDR) per 1000	
HDMI input ports quantity 2	2.0 2	hours AC input voltage AC input frequency Energy efficiency scale	100 - 240 V 50 - 60 Hz A to G
DVI port * DVI-I ports quantity	<b>✓</b> 1	Computer system	
USB ports quantity  USB ports quantity  USB version  2  20	<b>√</b> 2	Video formats supported Audio formats supported Image formats supported	H.264, M-JPEG, MPEG, WMV3 AAC, HE-AAC, WMA BMP, JPG, PNG
Ethernet LAN *	✓	Weight & dimensions	
Ethernet LAN (RJ-45) ports Audio (L/R) in Audio (L/R) out RS-232C	1 1 1	Display width Display depth Display height Display weight	1128.4 mm 63.5 mm 649 mm 14.8 kg
Remote (IR) input	1	Packaging content	
Remote (IR) output	1	Remote control included	✓
Audio		Batteries included	✓
Built-in speaker(s) *	<b>√</b> 2	Cables included	AC, IR sensor, RS-232, USB
Number of built-in speakers RMS rated power	2 20 W	Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 20 - 80%

Design		Operational conditions	
Product design *	Digital A-board	Storage temperature (T-T)	-20 - 60 °C
Placement supported *	on Horizontal/Vertical	Storage relative humidity (H-H)	5 - 95%
Orientation		Logistics data	
Product colour *		Harmonized System (HS) code	85285210





8712581778583

0685417580088



685417580088

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.